



EEM18DRSD Information

Heisener.com

Part Number EEM18DRSD

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 36POS 0.156

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TT 4	0D D 0D		
H) H) VI T	XDRSD	Specificat	ions

Manufacturer Part Number EEM18DRSD Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 18 Number of Positions 36 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Tin Contact Type Loop Bellows Color Blue Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	EEMIODROD Specifications		
Category Card Edge Connectors - Edgeboard Connectors Package Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 18 Number of Positions 36 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Tin Contact Finish Thickness 100µin (2.54µm) Contact Type Loop Bellows Color Blue Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer Part Number	EEM18DRSD	
Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 18 Number of Positions 36 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Tin Contact Finish Thickness 100µin (2.54µm) Contact Type Loop Bellows Color Blue Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer	Sullins Connector Solutions	
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 18 Number of Positions 36 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Thickness 100μin (2.54μm) Contact Type Loop Bellows Color Blue Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Category	Connectors, Interconnects	
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 18 Number of Positions 36 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Thickness 100µin (2.54µm) Contact Type Loop Bellows Color Blue Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia		Card Edge Connectors - Edgeboard Connectors	
Card Type	Package	-	
GenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100μin (2.54μm)Contact TypeLoop BellowsColorBlueFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Series	-	
Number of Positions 36 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Thickness 100µin (2.54µm) Contact Type Loop Bellows Color Blue Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Type	Non Specified - Dual Edge	
Number of Positions 36 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Tin Contact Finish Thickness 100μin (2.54μm) Contact Type Loop Bellows Color Blue Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Gender	Female	
Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Thickness 100µin (2.54µm) Contact Type Loop Bellows Color Blue Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions/Bay/Row	18	
Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Tin Contact Finish Thickness 100μin (2.54μm) Contact Type Loop Bellows Color Blue Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions	36	
Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Tin Contact Finish Thickness 100μin (2.54μm) Contact Type Loop Bellows Color Blue Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Thickness	0.062" (1.57mm)	
Features Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Tin Contact Finish Thickness 100µin (2.54µm) Contact Type Loop Bellows Color Blue Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Rows	2	
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100μin (2.54μm)Contact TypeLoop BellowsColorBlueFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Pitch	0.156" (3.96mm)	
Termination Solder Contact Material Phosphor Bronze Contact Finish Tin Contact Finish Thickness 100μin (2.54μm) Contact Type Loop Bellows Color Blue Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Features	-	
Contact Material Phosphor Bronze Contact Finish Tin Contact Finish Thickness 100µin (2.54µm) Contact Type Loop Bellows Color Blue Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Mounting Type	Through Hole	
Contact Finish Contact Finish Thickness 100μin (2.54μm) Contact Type Loop Bellows Color Blue Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Termination	Solder	
Contact Finish Thickness 100μin (2.54μm) Contact Type Loop Bellows Color Blue Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Material	Phosphor Bronze	
Contact Type Loop Bellows Color Blue Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish	Tin	
Color Blue Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish Thickness	100μin (2.54μm)	
Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Type	Loop Bellows	
	Color	Blue	
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	
	Operating Temperature	-65°C ~ 125°C	
Report errors		Report errors	s?

EEM18DRSD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EEM18DRSD Payment Methods





















EEM18DRSD Shipping Methods













If you have any question about EEM18DRSD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com