



### **EEM18DRUI Information**

Heisener.com

Part Number EEM18DRUI

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 36POS 0.156

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **EEM18DRUI Specifications**

Manufacturer Part Number         EEM18DRUI           Manufacturer         Sullins Connector Solutions           Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         18           Number of Positions         36           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.156" (3.96mm)           Features         -           Mounting Type         Through Hole           Contact Material         Phosphor Bronze           Contact Material         Phosphor Bronze           Contact Finish Thickness         100µin (2.54µm)           Contact Type         Full Bellows           Color         Blue           Flange Feature         Top Mount Opening, Threaded Insert, 4-40           Operating Temperature         -65°C ~ 125°C	EEMTODICT Specifications	
Category       Connectors, Interconnects         Package       -         Series       -         Card Type       Non Specified - Dual Edge         Gender       Female         Number of Positions/Bay/Row       18         Number of Positions       36         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.156" (3.96mm)         Features       -         Mounting Type       Through Hole         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Tin         Contact Type       Full Bellows         Color       Blue         Flange Feature       Top Mount Opening, Threaded Insert, 4-40         Operating Temperature       -65°C ~ 125°C	Manufacturer Part Number	EEM18DRUI
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100μin (2.54μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100μin (2.54μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         18           Number of Positions         36           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.156" (3.96mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Tin           Contact Finish Thickness         100μin (2.54μm)           Contact Type         Full Bellows           Color         Blue           Flange Feature         Top Mount Opening, Threaded Insert, 4-40           Operating Temperature         -65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100μin (2.54μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Package	-
Gender         Female           Number of Positions/Bay/Row         18           Number of Positions         36           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.156" (3.96mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Tin           Contact Finish Thickness         100µin (2.54µm)           Contact Type         Full Bellows           Color         Blue           Flange Feature         Top Mount Opening, Threaded Insert, 4-40           Operating Temperature         -65°C ~ 125°C	Series	-
Number of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100μin (2.54μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100μin (2.54μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100μin (2.54μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	18
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100μin (2.54μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions	36
Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100μin (2.54μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100μin (2.54μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100μin (2.54μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Pitch	0.156" (3.96mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100μin (2.54μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness $100\mu$ in (2.54 $\mu$ m)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature $-65^{\circ}$ C ~ $125^{\circ}$ C	Mounting Type	Through Hole
Contact Finish  Contact Finish Thickness $100\mu$ in (2.54 $\mu$ m)  Contact Type  Full Bellows  Color  Blue  Flange Feature  Top Mount Opening, Threaded Insert, 4-40  Operating Temperature  -65°C ~ 125°C	Termination	Solder
Contact Finish Thickness $100\mu$ in (2.54 $\mu$ m)  Contact Type Full Bellows  Color Blue  Flange Feature Top Mount Opening, Threaded Insert, 4-40  Operating Temperature -65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact Type Full Bellows  Color Blue  Flange Feature Top Mount Opening, Threaded Insert, 4-40  Operating Temperature -65°C ~ 125°C	Contact Finish	Tin
Color Blue  Flange Feature Top Mount Opening, Threaded Insert, 4-40  Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	100μin (2.54μm)
Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Blue
	Flange Feature	Top Mount Opening, Threaded Insert, 4-40
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

### **EEM18DRUI Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **EEM18DRUI Payment Methods**





















### **EEM18DRUI Shipping Methods**













If you have any question about EEM18DRUI, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com