

# EEM43DTMH-S189

### EEM43DTMH-S189 Information

Heisener.com	Part Number Manufacturer Category Description Package	EEM43DTMH-S189 Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 86POS 0.156 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **EEM43DTMH-S189** Specifications

Manufacturer Sullins Connectors Solutions   Category Connectors, Interconnects   Card Edge Connectors - Edgeboard Connectors Card Edge Connectors   Package -   Series -   Card Type Non Specified - Dual Edge   Gender Female   Number of Positions/Bay/Row 43   Number of Positions/Bay/Row 86   Card Thickness 0.062" (1.57mm)   Number of Rows 2   Pitch 0.156" (3.96mm)   Features -   Mounting Type Through Hole, Right Angle   Contact Material Polosphor Bronze   Contact Finish Thickness 100µin (2.54µm)   Contact Type Loop Bellows   Contact Type Solege Solutions   Color Bue			
CatagoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row43Number of Positions/Bay/Row86Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.156° (3.96mm)Features-Mounting TypeFinough Hole, Right AngleContact MaterialSolderContact Finish Thickness100µin (2.54µm)Contact TippLoop BellowsContact TypeLoop BellowsContact TypeBueContact TypeSolderContact TypeSolderContact TypeCoop BellowsContact TypeSolderContact TypeSolder	Manufacturer Part Number		
Card Edge Connectors - Edgeboard Connectors   Package -   Series -   Card Type Non Specified - Dual Edge   Gender Female   Number of Positions/Bay/Row 43   Number of Positions 86   Card Thickness 0.062" (1.57mm)   Number of Rows 2   Pitch 0.156" (3.96mm)   Features -   Mounting Type Through Hole, Right Angle   Contact Material Polyphor Bronze   Contact Finish Tin   Contact Type Loop Bellows   Color Bue   Color Bue   Flange Feature -   Operating Temperature -	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row43Scard Thickness0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish100µin (2.54µm)Contact Finish Thickness100µin (2.54µm)Contact TypeLoop BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row43Number of Positions86Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact Material9osphor BronzeContact Finish100µin (2.54µm)Contact Finish Thickness100µin (2.54µm)Contact TypeBueColorBueFlange Feature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card Type Non Specified - Dual Edge   Gender Female   Number of Positions/Bay/Row 43   Number of Positions/Bay/Row 86   Card Thickness 0.062" (1.57mm)   Number of Rows 2   Pitch 0.156" (3.96mm)   Features -   Mounting Type Through Hole, Right Angle   Young Hole, Right Angle Solder   Contact Material Foophon Bronze   Contact Finish Thickness 100µin (2.54µm)   Contact Type Loop Bellows   Color Bue   Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia   Operating Temperature -65°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row43Number of Positions86Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialPhosphor BronzeContact Finish Thickness100µin (2.54µm)Contact TypeLoop BellowsColorBlueFlange Feature-Operating Temperature-55°C ~ 125°C	Series	-	
Number of Positions/Bay/Row43Number of Positions86Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialPolsphor BronzeContact Finish Thickness100µin (2.54µm)Contact TypeLoop BellowsColorBlueFlarge FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions 86   Card Thickness 0.062" (1.57mm)   Number of Rows 2   Pitch 0.156" (3.96mm)   Features -   Mounting Type Through Hole, Right Angle   Termination Solder   Contact Material Phosphor Bronze   Contact Finish Thickness 100µin (2.54µm)   Contact Type Loop Bellows   Color Blue   Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeLoop BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	43	
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeLoop BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	86	
Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeLoop BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeLoop BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2	
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeLoop BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.156" (3.96mm)	
TerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeLoop BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-	
Contact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeLoop BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole, Right Angle	
Contact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeLoop BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder	
Contact Finish Thickness100µin (2.54µm)Contact TypeLoop BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact TypeLoop BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Tin	
ColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	100µin (2.54µm)	
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Loop Bellows	
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Blue	
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	-65°C ~ 125°C	
			Report errors?

#### **EEM43DTMH-S189** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## **EEM43DTMH-S189** Payment Methods





If you have any question about EEM43DTMH-S189, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com