

EEU-FR1A332B

quest a Quote

EEU-FR1A332B Information

	Part Number	EEU-FR1A332B	
	Manufacturer	Panasonic Electronic Components	
www.weener.com	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 3300UF 20% 10V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



EEU-FR1A332B Specifications

Manufacturer Panasonic Electronic Components Category Capacitors Atuminum Electrolytic Capacitors Atuminum Electrolytic Capacitors Package Radial, Can Series FR Capacitance 3300µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 10000 Hrs @ 105°C Operating Temperature 40°C ~ 105°C Polarization General Purpose Riple Current - Low Frequency 2.08A @ 120Hz Ripple Current - High Frequency 2.6A @ 100kHz Impedance 18 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Kieple Load Maxi 0.866" (22.00mm) Size / Dimension 0.492" Dia (12.50mm)		
CapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesFRCapacitance3300µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency2.08A @ 120HzRipple Current - High Frequency3.04 @ 100kHzLided Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Size / Dimension0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer Part Number	EEU-FR1A332B
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesFRCapacitance3300µFCapacitance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency2.08A @ 120HzRipple Current - High Frequency0.197" (5.00mm)Size / Dimension0.197" (5.00mm)Size / Dimension0.866" (22.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer	Panasonic Electronic Components
PackageRadial, CanSeriesFRCapacitance3300µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency2.08A @ 120HzImpedance18 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Category	Capacitors
SeriesFRCapacitance3300µFConsectance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency2.6A @ 100kHzImpedance18 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.866" (22.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		Aluminum Electrolytic Capacitors
Capacitance3300µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.08A @ 120HzLifed Spacing1197" (5.00mm)Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Size / Dimension0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Package	Radial, Can
Tolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency2.08A @ 120HzImpedance18 mOhmsLad Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Series	FR
Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.08A @ 120HzRipple Current - High Frequency2.6A @ 100kHzImpedance18 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Capacitance	3300µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature~40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.08A @ 120HzBipple Current - High Frequency2.6A @ 100kHzImpedance18 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.866" (22.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Tolerance	$\pm 20\%$
Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.08A @ 120HzRipple Current - High Frequency2.6A @ 100kHzImpedance18 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.866" (22.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Voltage - Rated	10V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.08A @ 120HzRipple Current - High Frequency2.6A @ 100kHzImpedance18 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency2.08A @ 120HzRipple Current - High Frequency2.6A @ 100kHzImpedance18 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lifetime @ Temp.	10000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.08A @ 120HzRipple Current - High Frequency2.6A @ 100kHzImpedance18 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Operating Temperature	$-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$
Ripple Current - Low Frequency2.08A @ 120HzRipple Current - High Frequency2.6A @ 100kHzImpedance18 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Polarization	Polar
In a first of the second sec	Applications	General Purpose
Impedance18 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	2.08A @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	2.6A @ 100kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	18 mOhms
Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole	Size / Dimension	0.492" Dia (12.50mm)
Mounting Type Through Hole	Height - Seated (Max)	0.866" (22.00mm)
	Surface Mount Land Size	-
Padiat Can	Mounting Type	Through Hole
Radial, Call	Package / Case	Radial, Can
Report errors?		Report errors?

EEU-FR1A332B Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

EEU-FR1A332B Payment Methods



EEU-FR1A332B Shipping Methods



If you have any question about EEU-FR1A332B, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com