



## **EEU-FS1A472 Information**

Heisener.com

Part Number EEU-FS1A472

Manufacturer Panasonic Electronic Components

**Category** Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** 10VDC, 4700UF, 10000H, 105DEGC

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **EEU-FS1A472 Specifications**

Manufacturer Part Number         EEU-FS1A472           Manufacturer         Panasonic Electronic Components           Category         Capacitors           Package         Radial, Can           Series         FS           Capacitance         4700µF           Tolerance         ±20%           Voltage - Rated         10V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp,         10000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         General Purpose           Ripple Current - Low Frequency         2.552A @ 120Hz           Ripple Current - High Frequency         3.19A @ 100kHz           Impedance         1.979" (5.00mm)           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	<b>-</b>	
Category         Capacitors           Package         Radial, Can           Series         FS           Capacitance         4700µF           Tolerance         ±20%           Voltage - Rated         10V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         10000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.552A @ 120Hz           Ripple Current - High Frequency         3.19A @ 100kHz           Impedance         15 mOhms           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	EEU-FS1A472
Package         Radial, Can           Series         FS           Capacitance         4700μF           Tolerance         ±20%           Voltage - Rated         10V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         10000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.552A @ 120Hz           Ripple Current - High Frequency         3.19A @ 100kHz           Impedance         15 mOhms           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer	Panasonic Electronic Components
Package         Radial, Can           Series         FS           Capacitance         4700µF           Tolerance         ±20%           Voltage - Rated         10V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         10000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.552A @ 120Hz           Ripple Current - High Frequency         3.19A @ 100kHz           Impedance         15 mOhms           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         FS           Capacitance         4700μF           Tolerance         ±20%           Voltage - Rated         10V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         10000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.552A @ 120Hz           Ripple Current - High Frequency         3.19A @ 100kHz           Impedance         15 mOhms           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance         4700µF           Tolerance         ±20%           Voltage - Rated         10V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         10000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.552A @ 120Hz           Ripple Current - High Frequency         3.19A @ 100kHz           Impedance         15 mOhms           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 10V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 10000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose Ripple Current - Low Frequency 2.552A @ 120Hz Ripple Current - High Frequency 3.19A @ 100kHz  Impedance 15 mOhms  Lead Spacing 0.197" (5.00mm)  Size / Dimension 0.492" Dia (12.50mm)  Height - Seated (Max) 1.063" (27.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Series	FS
Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.552A @ 120HzRipple Current - High Frequency3.19A @ 100kHzImpedance15 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	4700μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  2.552A @ 120Hz  Ripple Current - High Frequency  3.19A @ 100kHz  Impedance  15 mOhms  Lead Spacing  0.197" (5.00mm)  Size / Dimension  Height - Seated (Max)  1.063" (27.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  3.19A @ 100kHz  Impedance  Lead Spacing  0.197" (5.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  10000 Hrs @ 105°C  -40°C ~ 105	Voltage - Rated	10V
Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.552A @ 120Hz  Ripple Current - High Frequency 3.19A @ 100kHz  Impedance 15 mOhms  Lead Spacing 0.197" (5.00mm)  Size / Dimension 0.492" Dia (12.50mm)  Height - Seated (Max) 1.063" (27.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.552A @ 120Hz Ripple Current - High Frequency 3.19A @ 100kHz Impedance 15 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	10000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 2.552A @ 120Hz Ripple Current - High Frequency 3.19A @ 100kHz Impedance 15 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  3.19A @ 100kHz  Impedance  15 mOhms  Lead Spacing  0.197" (5.00mm)  Size / Dimension  0.492" Dia (12.50mm)  Height - Seated (Max)  1.063" (27.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance 15 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance15 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	2.552A @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	3.19A @ 100kHz
Size / Dimension 0.492" Dia (12.50mm)  Height - Seated (Max) 1.063" (27.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	15 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size -  Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **EEU-FS1A472 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **EEU-FS1A472 Payment Methods**



















### **EEU-FS1A472 Shipping Methods**













If you have any question about EEU-FS1A472, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com