



### **EEU-FS1V182SB Information**

Heisener.com

Part Number EEU-FS1V182SB

Manufacturer Panasonic Electronic Components

Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** 35VDC, 1800UF, 10000H, 105DEGC,

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **EEU-FS1V182SB Specifications**

Manufacturer Part NumberEEU-FS1V182SBManufacturerPanasonic Electronic ComponentsCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesFSCapacitance1800μFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.64A @ 120HzRipple Current - High Frequency3.3A @ 100kHzImpedance17 mOhmsLead Spacing0.295" (7.49mm)
Category Capacitors Aluminum Electrolytic Capacitors  Package Radial, Can  Series FS Capacitance 1800μF  Tolerance ±20% Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 10000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Inpedance 17 mOhms
Aluminum Electrolytic Capacitors  Package Radial, Can  Series FS  Capacitance 1800µF  Tolerance ±20%  Voltage - Rated 35V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 10000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.64A @ 120Hz  Ripple Current - High Frequency 17 mOhms
Package Series FS Capacitance 1800µF Tolerance ±20% Voltage - Rated SSR (Equivalent Series Resistance) Lifetime @ Temp. 10000 Hrs @ 105°C Operating Temperature Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Inpedance Radial, Can FS Redial, Can FS S Redial FS S S Redial FS S S Redial FS S R
SeriesFSCapacitance1800μFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.64A @ 120HzRipple Current - High Frequency3.3A @ 100kHzImpedance17 mOhms
Capacitance 1800µF  Tolerance ±20%  Voltage - Rated 35V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 10000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.64A @ 120Hz  Ripple Current - High Frequency 3.3A @ 100kHz  Impedance 17 mOhms
Tolerance ±20%  Voltage - Rated 35V  ESR (Equivalent Series Resistance) -  Lifetime @ Temp. 10000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.64A @ 120Hz  Ripple Current - High Frequency 3.3A @ 100kHz  Impedance 17 mOhms
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  10000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  3.3A @ 100kHz  Impedance  17 mOhms
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  10000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  3.3A @ 100kHz  Impedance  17 mOhms
Lifetime @ Temp. 10000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.64A @ 120Hz  Ripple Current - High Frequency 3.3A @ 100kHz  Impedance 17 mOhms
Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  3.3A @ 100kHz  Impedance  17 mOhms
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.64A @ 120Hz Ripple Current - High Frequency 3.3A @ 100kHz Impedance 17 mOhms
Applications General Purpose Ripple Current - Low Frequency 2.64A @ 120Hz Ripple Current - High Frequency 3.3A @ 100kHz Impedance 17 mOhms
Ripple Current - Low Frequency  Ripple Current - High Frequency  3.3A @ 100kHz  Impedance  17 mOhms
Ripple Current - High Frequency 3.3A @ 100kHz Impedance 17 mOhms
Impedance 17 mOhms
Load Spacing 0.205" (7.40mm)
Lead Spacing 0.295" (7.49mm)
Size / Dimension 0.630" Dia (16.00mm)
Height - Seated (Max) 0.866" (22.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can
Report errors?

#### **EEU-FS1V182SB Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **EEU-FS1V182SB Payment Methods**

































If you have any question about EEU-FS1V182SB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com