



EEU-HD1A103 Information

Part Number EEU-HD1A103

Manufacturer Panasonic Electronic Components

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 10000UF 20% 10V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EEU-HD1A103 Specifications

Manufacturer Part NumberEEU-HD1A103ManufacturerPanasonic Electronic ComponentsCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesHDCapacitance10000µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifettime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.89A @ 120HzRipple Current - High Frequency2.174A @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)	<u> </u>	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series HD Capacitance 10000μF Tolerance ±20% Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Line (100 Hrs @ 100 Hrs (100 Hr	Manufacturer Part Number	EEU-HD1A103
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesHDCapacitance10000μFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.89A @ 120HzRipple Current - High Frequency2.174A @ 100kHzImpedance-	Manufacturer	Panasonic Electronic Components
PackageRadial, CanSeriesHDCapacitance10000μFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.89A @ 120HzRipple Current - High Frequency2.174A @ 100kHzImpedance-	Category	Capacitors
SeriesHDCapacitance10000μFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.89A @ 120HzRipple Current - High Frequency2.174A @ 100kHzImpedance-		Aluminum Electrolytic Capacitors
Capacitance10000μFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.89A @ 120HzRipple Current - High Frequency2.174A @ 100kHzImpedance-	Package	Radial, Can
Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.89A @ 120Hz Ripple Current - High Frequency 2.174A @ 100kHz Impedance -	Series	HD
Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.89A @ 120HzRipple Current - High Frequency2.174A @ 100kHzImpedance-	Capacitance	10000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 1.89A @ 120Hz Ripple Current - High Frequency 2.174A @ 100kHz Impedance -	Tolerance	±20%
Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.89A @ 120Hz Ripple Current - High Frequency 2.174A @ 100kHz Impedance -	Voltage - Rated	10V
Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 2.174A @ 100kHz Impedance -	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.89A @ 120Hz Ripple Current - High Frequency 2.174A @ 100kHz Impedance -	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 1.89A @ 120Hz Ripple Current - High Frequency 2.174A @ 100kHz Impedance -	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 1.89A @ 120Hz 2.174A @ 100kHz -	Polarization	Polar
Ripple Current - High Frequency 2.174A @ 100kHz Impedance -	Applications	General Purpose
Impedance -	Ripple Current - Low Frequency	1.89A @ 120Hz
	Ripple Current - High Frequency	2.174A @ 100kHz
Lead Spacing 0.295" (7.50mm)	Impedance	-
	Lead Spacing	0.295" (7.50mm)
Size / Dimension 0.630" Dia (16.00mm)	Size / Dimension	0.630" Dia (16.00mm)
Height - Seated (Max) 1.063" (27.00mm)	Height - Seated (Max)	1.063" (27.00mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

EEU-HD1A103 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EEU-HD1A103 Payment Methods



















EEU-HD1A103 Shipping Methods













If you have any question about EEU-HD1A103, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com