



### **EEU-HD1H100 Information**

Part Number EEU-HD1H100

Manufacturer Panasonic Electronic Components

**Category** Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 10UF 20% 50V RADIAL

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

www.helsener

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **EEU-HD1H100 Specifications**

Manufacturer Part Number         EEU-HD1H100           Manufacturer         Panasonic Electronic Components           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can           Series         HD           Capacitance         10µF           Tolerance         ±20%           Voltage - Rated         50V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         100 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         39mA @ 120Hz           Ripple Current - High Frequency         78mA @ 100kHz           Impedance         -           Lead Spacing         0.098" (2.50mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	<b>-</b>	
Category         Capacitors           Package         Radial, Can           Series         HD           Capacitance         10μF           Tolerance         ±20%           Voltage - Rated         50V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         39mA @ 120Hz           Ripple Current - High Frequency         78mA @ 100kHz           Impedance         -           Lead Spacing         0.098" (2.50mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	EEU-HD1H100
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesHDCapacitance10μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency39mA @ 120HzRipple Current - High Frequency78mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Panasonic Electronic Components
PackageRadial, CanSeriesHDCapacitance10μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency39mA @ 120HzRipple Current - High Frequency78mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesHDCapacitance10μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency39mA @ 120HzRipple Current - High Frequency78mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can		Aluminum Electrolytic Capacitors
Capacitance         10μF           Tolerance         ±20%           Voltage - Rated         50V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         39mA @ 120Hz           Ripple Current - High Frequency         78mA @ 100kHz           Impedance         -           Lead Spacing         0.098" (2.50mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 50V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C  Operating Temperature -55°C ~ 105°C  Polarization Polar  Applications General Purpose Ripple Current - Low Frequency 39mA @ 120Hz  Ripple Current - High Frequency 78mA @ 100kHz  Impedance - Lead Spacing 0.098" (2.50mm)  Size / Dimension 0.197" Dia (5.00mm)  Height - Seated (Max) 0.492" (12.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Series	HD
Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency39mA @ 120HzRipple Current - High Frequency78mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	10μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  1000 Hrs @ 105°C  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  39mA @ 120Hz  Ripple Current - High Frequency  78mA @ 100kHz  Impedance  -  Lead Spacing  0.098" (2.50mm)  Size / Dimension  0.197" Dia (5.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Polar  -55°C ~ 105°C  -6000  General Purpose  39mA @ 120Hz  78mA @ 100kHz  -78mA @ 100kHz  -78	Voltage - Rated	50V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Row	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 39mA @ 120Hz Ripple Current - High Frequency 78mA @ 100kHz Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  78mA @ 100kHz  Impedance  Lead Spacing  0.098" (2.50mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  General Purpose  39mA @ 120Hz  78mA @ 100kHz  -  0.098" (2.50mm)  0.492" (12.50mm)  Through Hole  Radial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 78mA @ 100kHz Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.098" (2.50mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	39mA @ 120Hz
Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	78mA @ 100kHz
Size / Dimension 0.197" Dia (5.00mm)  Height - Seated (Max) 0.492" (12.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.492" (12.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
	Package / Case	Radial, Can
Report errors?		Report errors?

### **EEU-HD1H100 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **EEU-HD1H100 Payment Methods**



















### **EEU-HD1H100 Shipping Methods**













If you have any question about EEU-HD1H100, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com