



EEU-TA1C102 Information

Heisener.com

Part Number EEU-TA1C102

Manufacturer Panasonic Electronic Components

Category Capacitors

Aluminum Electrolytic Capacitors

CAP ALUM 1000UF 20% 16V RADIAL **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EEU-TA1C102 Specifications

Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series TA Capacitance 1000μF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.118A @ 120Hz Ripple Current - High Frequency 1.49A @ 100kHz Impedance 42 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size -	_	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series TA Capacitance 1000µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.118A @ 120Hz Ripple Current - High Frequency 1.49A @ 100kHz Impedance 42 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	EEU-TA1C102
Package Radial, Can Series TA Capacitance 1000μF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.118A @ 120Hz Ripple Current - High Frequency 1.49A @ 100kHz Impedance 42 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Panasonic Electronic Components
Package Radial, Can Series TA Capacitance 1000µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.118A @ 120Hz Ripple Current - High Frequency 1.49A @ 100kHz Impedance 42 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series TA Capacitance 1000µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.118A @ 120Hz Ripple Current - High Frequency 1.49A @ 100kHz Impedance 42 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 1000μF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.118A @ 120Hz Ripple Current - High Frequency 1.49A @ 100kHz Impedance 42 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.118A @ 120Hz Ripple Current - High Frequency 1.49A @ 100kHz Impedance 42 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	TA
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 1.118A @ 120Hz Rippedance 42 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Polor Height - Seated (Max) Radial, Can	Capacitance	1000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Applications General Purpose Ripple Current - Low Frequency 1.118A @ 120Hz Ripple Current - High Frequency 1.49A @ 100kHz Impedance 42 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.118A @ 120Hz Ripple Current - High Frequency 1.49A @ 100kHz Impedance 42 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Polar 2000 Hrs @ 125°C -40°C ~ 125°C -40	Voltage - Rated	16V
Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.118A @ 120Hz Ripple Current - High Frequency 1.49A @ 100kHz Impedance 42 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.118A @ 120Hz Ripple Current - High Frequency 1.49A @ 100kHz Impedance 42 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 125°C
Applications General Purpose Ripple Current - Low Frequency 1.118A @ 120Hz Ripple Current - High Frequency 1.49A @ 100kHz Impedance 42 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 125°C
Ripple Current - Low Frequency Ripple Current - High Frequency 1.49A @ 100kHz Impedance 42 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency 1.49A @ 100kHz Impedance 42 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance 42 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	1.118A @ 120Hz
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	1.49A @ 100kHz
Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	42 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.866" (22.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

EEU-TA1C102 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EEU-TA1C102 Payment Methods



















EEU-TA1C102 Shipping Methods













If you have any question about EEU-TA1C102, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com