

EEU-TA1H221

equest a Quote

EEU-TA1H221 Information

| Contraction of the second seco | Part Number | EEU-TA1H221 |
|--|--------------|---|
| | Manufacturer | Panasonic Electronic Components |
| | Category | Capacitors Aluminum Electrolytic Capacitors |
| | Description | CAP ALUM 220UF 20% 50V RADIAL |
| | Package | Radial, Can |
| | | For the pricing/inventory/lead time, please contact us |
| For Reference Only | | Website: https://www.heisener.com E-mail: salesdept@heisener.com |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



EEU-TA1H221 Specifications

| Manufacturer Part Number EEU-TA1H221 Manufacturer Panasonic Electronic Components Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series TA Capacitance 20µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature 40°C - 125°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency 604.5mA @ 120Hz Impedance 100 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Size / Dimension 0.394" Dia (10.00mm) Size / Dimension 0.394" Dia (10.00mm) Size / Dimension 7.500mm) Size / Dimension 7.500mm) Size / Dimension 0.394" Dia (10.00mm) Size / Dimension 7.500mm) Size / Dime | | |
|---|------------------------------------|----------------------------------|
| Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series TA Capacitance 20µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature 40°C ~ 125°C Polarization General Purpose Applications General Purpose Ripple Current - High Frequency 604.5mA @ 120Hz Impedance 100 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Lied Spacing 0.566" (22.00mm) Surface Mount Land Size - Mounting Type Finough Hole | Manufacturer Part Number | EEU-TA1H221 |
| AckageAluninum Electrolytic CapacitorsPackageRadial, CanSeriesTACapacitance220µFTolerance±20%Voltage - Rated50 VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature40°C ~ 125°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency604.5mA @ 120HzImpedance100 mOhmsLead Spacing0.394° Dia(10.00mm)Size / Dimension0.394° Dia(10.00mm)Size / Dimension0.366° (22.00mm)Surface Mount Land Size-Mounting TypeRadial, Can | Manufacturer | Panasonic Electronic Components |
| PackageRadial, CanSeriesTACapacitance220µFTolerance±20%Voltage Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature40°C ~ 125°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency604.5mA @ 120HzImpedance100 mOhmsLiad Spacing0.394° Dia(1.00mm)Size / Dimension0.394° Dia(1.00mm)Size / Dimension0.366° (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Category | Capacitors |
| SeriesTACapacitance220µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature40°C ~ 125°CPolarizationGeneral PurposeApplications64.5mA @ 120HzRipple Current - Low Frequency604.5mA @ 120HzImpedance100 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.366" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can | | Aluminum Electrolytic Capacitors |
| Capacitance20µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature40°C ~ 125°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency930mA @ 100kHzImpedance100 mOhmsLiad Spacing0.197° (5.00mm)Size / Dimension0.394° Dia (10.00mm)Size / Dimension0.366° (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can | Package | Radial, Can |
| Tolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature40°C ~ 125°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency604.5mA @ 120HzImpedance100 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Hounting TypeThrough HolePackage / CaseKatial, Can | Series | ТА |
| Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature40°C ~ 125°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency604.5mA @ 120HzMipedance100 mOhmsImpedance0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeFnough HelePackage / CaseRadial, Can | Capacitance | 220µF |
| ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency604.5rnA @ 120HzMipedance930mA @ 100kHzLead Spacing0.197" (5.00mm)Size / Dinension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRaid, Can | Tolerance | ±20% |
| Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency604.5mA @ 120HzNipedance100 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Voltage - Rated | 50V |
| Operating Temperature-40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency604.5mA @ 120HzRipple Current - High Frequency930mA @ 100kHzImpedance100 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRadial, Can | ESR (Equivalent Series Resistance) | - |
| PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency604.5mA @ 120HzRipple Current - High Frequency930mA @ 100kHzImpedance100 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Lifetime @ Temp. | 2000 Hrs @ 125°C |
| ApplicationsGeneral PurposeRipple Current - Low Frequency604.5mA @ 120HzRipple Current - High Frequency930mA @ 100kHzImpedance100 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadia, Can | Operating Temperature | -40°C ~ 125°C |
| Ripple Current - Low Frequency604.5mA @ 120HzRipple Current - High Frequency930mA @ 100kHzImpedance100 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Polarization | Polar |
| Ripple Current - High Frequency930mA @ 100kHzImpedance100 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Applications | General Purpose |
| Interface100 mOhmsImpedance100 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Ripple Current - Low Frequency | 604.5mA @ 120Hz |
| Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Ripple Current - High Frequency | 930mA @ 100kHz |
| Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Impedance | 100 mOhms |
| Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Lead Spacing | 0.197" (5.00mm) |
| Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Size / Dimension | 0.394" Dia (10.00mm) |
| Mounting TypeThrough HolePackage / CaseRadial, Can | Height - Seated (Max) | 0.866" (22.00mm) |
| Package / Case Radial, Can | Surface Mount Land Size | - |
| | Mounting Type | Through Hole |
| Report errors? | Package / Case | Radial, Can |
| | | Report errors? |

EEU-TA1H221 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

EEU-TA1H221 Payment Methods



EEU-TA1H221 Shipping Methods



If you have any question about EEU-TA1H221, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com