



EEU-TP1V271B Information



For Reference Only

Part Number EEU-TP1V271B

Manufacturer Panasonic Electronic Components

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 270UF 20% 35V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EEU-TP1V271B Specifications

Manufacturer Part Number Manufacturer Panasonic Electronic Components Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can TP Capacitance 270µF Tolerance ½20% Voltage - Rated £5K (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing D.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Radial, Can Report errors? Radial, Can Report errors?	_	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series TP Capacitance 270μF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 130 mOhm Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -40°C ~ 135°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 715mA @ 120Hz Ripple Current - High Frequency 945mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	EEU-TP1V271B
Package Radial, Can Series TP Capacitance 270µF Tolerance ±20% Voltage - Rated 35 V ESR (Equivalent Series Resistance) 130 mOhm Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -40°C ~ 135°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 715mA @ 120Hz Ripple Current - High Frequency 945mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Panasonic Electronic Components
PackageRadial, CanSeriesTPCapacitance270μFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)130 mOhmLifetime @ Temp.3000 Hrs @ 125°COperating Temperature-40°C ~ 135°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency715mA @ 120HzRipple Current - High Frequency945mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
Series TP Capacitance 270μF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 130 mOhm Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -40°C ~ 135°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 715mA @ 120Hz Ripple Current - High Frequency 945mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 270μF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 130 mOhm Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -40°C ~ 135°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 715mA @ 120Hz Ripple Current - High Frequency 945mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 130 mOhm Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -40°C ~ 135°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 715mA @ 120Hz Ripple Current - High Frequency 945mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	TP
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 135°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Pagance Lead Spacing O.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 130 mOhm 305V 130 mOhm 6125°C -40°C ~ 135°C 6eneral Purpose General Purpose 715mA @ 120Hz 715mA @ 120Hz 945mA @ 100kHz 100mm) 10.394" (5.00mm) 10.394" (5.00mm) 10.394" (17.50mm) 10.689" (17.50mm) 10.689" (17.50mm) 10.689" (17.50mm) 10.689" (17.50mm)	Capacitance	270μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 135°C Polarization Applications General Purpose Ripple Current - Low Frequency 715mA @ 120Hz Ripple Current - High Frequency 945mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 135°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Polar Applications Ripple Current - High Frequency Polar 100kHz Polar 100kHz Polar 110mpedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Voltage - Rated	35V
Operating Temperature -40°C ~ 135°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 715mA @ 120Hz Ripple Current - High Frequency 945mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	130 mOhm
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 715mA @ 120Hz Ripple Current - High Frequency 945mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	3000 Hrs @ 125°C
Applications General Purpose Ripple Current - Low Frequency 715mA @ 120Hz Ripple Current - High Frequency 945mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 135°C
Ripple Current - Low Frequency Ripple Current - High Frequency 945mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency 945mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	715mA @ 120Hz
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	945mA @ 100kHz
Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.689" (17.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

EEU-TP1V271B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EEU-TP1V271B Payment Methods





















EEU-TP1V271B Shipping Methods













If you have any question about EEU-TP1V271B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com