



EEU-TP1V821 Information



For Reference Only

Part Number EEU-TP1V821

Manufacturer Panasonic Electronic Components

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 820UF 20% 35V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EEU-TP1V821 Specifications

Manufacturer Part NumberEEU-TPIV821ManufacturerPanasonic Electronic ComponentsCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesTPCapacitance\$20µFTolerance±20%Voltage - Rated35 VESR (Equivalent Series Resistance)30 mOhmLifetime @ Temp.4000 Hrs @ 125°COperating Temperature-40°C ~ 135°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.635A @ 120HzRipple Current - High Frequency1.75A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series TP Capacitance 820µF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 30 mOhm Lifetime @ Temp. 4000 Hrs @ 125°C Operating Temperature -40°C ~ 135°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.635A @ 120Hz Ripple Current - High Frequency 1.75A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size -	Manufacturer Part Number	EEU-TP1V821
Package Radial, Can Series TP Capacitance 820µF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 30 mOhm Lifetime @ Temp. 4000 Hrs @ 125°C Operating Temperature -40°C ~ 135°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.635A @ 120Hz Ripple Current - High Frequency 1.75A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) Surface Mount Land Size -	Manufacturer	Panasonic Electronic Components
PackageRadial, CanSeriesTPCapacitance\$20µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)30 mOhmLifetime @ Temp.4000 Hrs @ 125°COperating Temperature-40°C ~ 135°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.635A @ 120HzRipple Current - High Frequency1.75A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-	Category	Capacitors
Series TP Capacitance 820μF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 30 mOhm Lifetime @ Temp. 4000 Hrs @ 125°C Operating Temperature -40°C ~ 135°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.635A @ 120Hz Ripple Current - High Frequency 1.75A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size -		Aluminum Electrolytic Capacitors
Capacitance820µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)30 mOhmLifetime @ Temp.4000 Hrs @ 125°COperating Temperature-40°C ~ 135°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.635A @ 120HzRipple Current - High Frequency1.75A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-	Package	Radial, Can
Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 30 mOhm Lifetime @ Temp. 4000 Hrs @ 125°C Operating Temperature -40°C ~ 135°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.635A @ 120Hz Ripple Current - High Frequency 1.75A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size -	Series	TP
Voltage - Rated SSR (Equivalent Series Resistance) 30 mOhm Lifetime @ Temp. 4000 Hrs @ 125°C Operating Temperature -40°C ~ 135°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.635A @ 120Hz Ripple Current - High Frequency 1.75A @ 100kHz Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) Surface Mount Land Size -	Capacitance	820μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 4000 Hrs @ 125°C Operating Temperature -40°C ~ 135°C Polarization Applications General Purpose Ripple Current - Low Frequency 1.635A @ 120Hz Ripple Current - High Frequency 1.75A @ 100kHz Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) Surface Mount Land Size -	Tolerance	±20%
Lifetime @ Temp. 4000 Hrs @ 125°C Operating Temperature -40°C ~ 135°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.635A @ 120Hz Ripple Current - High Frequency 1.75A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size -	Voltage - Rated	35V
Operating Temperature -40°C ~ 135°C Polarization Applications General Purpose Ripple Current - Low Frequency 1.635A @ 120Hz Ripple Current - High Frequency 1.75A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size -	ESR (Equivalent Series Resistance)	30 mOhm
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.635A @ 120Hz Ripple Current - High Frequency 1.75A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size -	Lifetime @ Temp.	4000 Hrs @ 125°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 1.635A @ 120Hz 1.75A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size -	Operating Temperature	-40°C ~ 135°C
Ripple Current - Low Frequency Ripple Current - High Frequency 1.635A @ 120Hz 1.75A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size -	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size 1.75A @ 100kHz - 0.197" (5.00mm) 0.492" Dia (12.50mm) 1.063" (27.00mm)	Applications	General Purpose
Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size -	Ripple Current - Low Frequency	1.635A @ 120Hz
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size -	Ripple Current - High Frequency	1.75A @ 100kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-	Impedance	-
Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size -	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size -	Size / Dimension	0.492" Dia (12.50mm)
	Height - Seated (Max)	1.063" (27.00mm)
	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

EEU-TP1V821 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EEU-TP1V821 Payment Methods



















EEU-TP1V821 Shipping Methods













If you have any question about EEU-TP1V821, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com