



EEU-TP1V821B Information



For Reference Only

Part Number EEU-TP1V821B

Manufacturer Panasonic Electronic Components

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 820UF 20% 35V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EEU-TP1V821B Specifications

Manufacturer Part NumberEEU-TPI V821BManufacturerPanasonic Electronic ComponentsCategoryCapacitorsPackageRadial, CanSeriesTPCapacitance820µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)30 mOhmLifetime @ Temp.4000 Hrs @ 125°COperating Temperature-40°C ~ 135°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.635A @ 120HzRipple Current - High Frequency1.75A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)	-	
Category Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can From Capacitance Radial, Can TP Capacitance Radial, Can Series TP Capacitance Radial, Can Somethan Capacitance Radial, Can Somethan Capacitance Radial, Can Somethan Capacitance Radial, Can Radial, Can Radial, Can R	Manufacturer Part Number	EEU-TP1V821B
PackageRadial, CanSeriesTPCapacitance820μFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)30 mOhmLifetime @ Temp.4000 Hrs @ 125°COperating Temperature-40°C ~ 135°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.635A @ 120HzRipple Current - High Frequency1.75A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)	Manufacturer	Panasonic Electronic Components
PackageRadial, CanSeriesTPCapacitance820μFTolerance±20%Voltage - Rated35 VESR (Equivalent Series Resistance)30 mOhmLifetime @ Temp.4000 Hrs @ 125 °COperating Temperature-40 °C ~ 135 °CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.635 A @ 120 HzRipple Current - High Frequency1.75 A @ 100 kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)	Category	Capacitors
Series TP Capacitance 820μF Tolerance ±20% Voltage - Rated 35 V ESR (Equivalent Series Resistance) 30 mOhm Lifetime @ Temp. 4000 Hrs @ 125°C Operating Temperature -40°C ~ 135°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.635A @ 120Hz Ripple Current - High Frequency 1.75A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm)		Aluminum Electrolytic Capacitors
Capacitance820µFTolerance±20%Voltage - Rated35 VESR (Equivalent Series Resistance)30 mOhmLifetime @ Temp.4000 Hrs @ 125°COperating Temperature-40°C ~ 135°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.635A @ 120HzRipple Current - High Frequency1.75A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)	Package	Radial, Can
Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 30 mOhm Lifetime @ Temp. 4000 Hrs @ 125°C Operating Temperature -40°C ~ 135°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.635A @ 120Hz Ripple Current - High Frequency 1.75A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm)	Series	TP
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Lead Spacing Outper Spacing Size / Dimension 35V 35V 36V 36N 36N 36N 36N 36N 4000 Hrs @ 125°C -40°C ~ 135°C Polar General Purpose 1.635A @ 120Hz 1.75A @ 100kHz	Capacitance	820μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 4000 Hrs @ 125°C Operating Temperature -40°C ~ 135°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.635A @ 120Hz Ripple Current - High Frequency 1.75A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 30 mOhm 4000 Hrs @ 125°C -40°C ~ 135°C -4	Tolerance	±20%
Lifetime @ Temp. 4000 Hrs @ 125°C Operating Temperature -40°C ~ 135°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.635A @ 120Hz Ripple Current - High Frequency 1.75A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm)	Voltage - Rated	35V
Operating Temperature -40°C ~ 135°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.635A @ 120Hz Ripple Current - High Frequency 1.75A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm)	ESR (Equivalent Series Resistance)	30 mOhm
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.635A @ 120Hz Ripple Current - High Frequency 1.75A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm)	Lifetime @ Temp.	4000 Hrs @ 125°C
Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 1.75A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension O.492" Dia (12.50mm)	Operating Temperature	-40°C ~ 135°C
Ripple Current - Low Frequency Ripple Current - High Frequency 1.635A @ 120Hz 1.75A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm)	Polarization	Polar
Ripple Current - High Frequency 1.75A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm)	Applications	General Purpose
Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm)	Ripple Current - Low Frequency	1.635A @ 120Hz
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm)	Ripple Current - High Frequency	1.75A @ 100kHz
Size / Dimension 0.492" Dia (12.50mm)	Impedance	-
	Lead Spacing	0.197" (5.00mm)
Height - Seated (Max) 1.063" (27.00mm)	Size / Dimension	0.492" Dia (12.50mm)
	Height - Seated (Max)	1.063" (27.00mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

EEU-TP1V821B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EEU-TP1V821B Payment Methods





















EEU-TP1V821B Shipping Methods













If you have any question about EEU-TP1V821B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com