



EEV-HB0J101P Information



For Reference Only

Part Number EEV-HB0J101P

Manufacturer Panasonic Electronic Components

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 100UF 20% 6.3V SMD

Package Radial, Can - SMD

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EEV-HB0J101P Specifications

Manufacturer Part Number EEV-HB0J10IP Manufacturer Panasonic Electronic Components Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - SMD Series Automotive, AEC-Q200, HB Capacitance 100µF Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 7 ImA @ 120Hz Ripple Current - High Frequency - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.228" (5.80mm) Surface Mount Land Size 0.260" Lx 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	*	
Category Capacitors Package Radial, Can - SMD Series Automotive, AEC-Q200, HB Capacitance 100µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 71mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.228" (5.80mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Manufacturer Part Number	EEV-HB0J101P
Package Radial, Can - SMD Series Automotive, AEC-Q200, HB Capacitance 100μF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 71mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.228" (5.80mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Manufacturer	Panasonic Electronic Components
PackageRadial, Can - SMDSeriesAutomotive, AEC-Q200, HBCapacitance 100μ FTolerance $\pm 20\%$ Voltage - Rated $6.3V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $2000 \text{ Hrs @ } 105^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency71mA @ 120HzRipple Current - High Frequency-Lead Spacing-Size / Dimension 0.248° Dia (6.30mm) Height - Seated (Max) 0.228° (5.80mm)Surface Mount Land Size 0.260° L x 0.260° W $(6.60\text{mm x } 6.60\text{mm})$ Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Category	Capacitors
SeriesAutomotive, AEC-Q200, HBCapacitance100μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency71mA @ 120HzRipple Current - High Frequency-Lead Spacing-Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.228" (5.80mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD		Aluminum Electrolytic Capacitors
Capacitance 100µF Tolerance ±20% Voltage - Rated 6.3 V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 71mA @ 120Hz Ripple Current - High Frequency - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.228" (5.80mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Package	Radial, Can - SMD
Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 71mA @ 120Hz Ripple Current - High Frequency - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.228" (5.80mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Series	Automotive, AEC-Q200, HB
Voltage - Rated6.3 VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency71mA @ 120HzRipple Current - High Frequency-Lead Spacing-Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.228" (5.80mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Capacitance	100μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Surface Mount Package / Case - 2000 Hrs @ 105°C -40°C ~ 105°C -4	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size O.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Package / Case Radial, Can - SMD	Voltage - Rated	6.3V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Pockage / Case Polar -40°C ~ 105°C Polar Automotive - 71mA @ 120Hz	ESR (Equivalent Series Resistance)	-
Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Polar Automotive 71mA @ 120Hz - 1. 2. 3. 4. 5. 4. 5. 5. 5. 6. 6. 7. 8. 8. 8. 8. 9. 9. 9. 9. 9. 9	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Automotive 71mA @ 120Hz - 1000	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Surface Mount Package / Case 71mA @ 120Hz - 71mA @ 120Hz 71mA @ 120Hz - 0.248" Dia (6.30mm) 0.248" Dia (6.30mm) 0.228" (5.80mm) 0.228" (5.80mm) Surface Mount Radial, Can - SMD	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension O.248" Dia (6.30mm) Height - Seated (Max) O.228" (5.80mm) Surface Mount Land Size O.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Applications	Automotive
Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.228" (5.80mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Ripple Current - Low Frequency	71mA @ 120Hz
Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.228" (5.80mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Ripple Current - High Frequency	-
Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.228" (5.80mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Impedance	-
Height - Seated (Max) Surface Mount Land Size 0.228" (5.80mm) 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Lead Spacing	-
Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Size / Dimension	0.248" Dia (6.30mm)
Mounting Type Surface Mount Package / Case Radial, Can - SMD	Height - Seated (Max)	0.228" (5.80mm)
Package / Case Radial, Can - SMD	Surface Mount Land Size	0.260" L x 0.260" W (6.60mm x 6.60mm)
	Mounting Type	Surface Mount
Report errors?	Package / Case	Radial, Can - SMD
		Report errors?

EEV-HB0J101P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EEV-HB0J101P Payment Methods



















EEV-HB0J101P Shipping Methods













If you have any question about EEV-HB0J101P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com