

EEV-TG1V101UP

EEV-TG1V101UP Information



Part Number	EEV-TG1V101UP	
Manufacturer	Panasonic Electronic Components	
Category	Capacitors Aluminum Electrolytic Capacitors	
Description	CAP ALUM 100UF 20% 35V SMD	
Package	Radial, Can - SMD	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



EEV-TG1V101UP Specifications

Manufacturer Part NumberEEV-TGIVI0IUPManufacturerPanasonic Electronic ComponentsCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesAutomotive, AEC-Q200, TGCapacitance100µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)500 Hrs @125°COperating Temperature40°C ~ 125°CPolarizon100µFApplicationsGeneral PurposeRiple Current - Low Frequency108 and 200 Hrs @120HzImpedance-Laed Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Mounting TypeSurface MountMounting TypeSurface MountPart merer300 Hrs @200 Hrs @20			
Category Capacitors Auminum Electrolytic Capacitors Package Radial, Can - SMD Series Automotive, AEC-Q200, TG Capacitance 100µF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 500 mOhm @ 100kHz Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature 40°C ~ 125°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency 197mA @ 100kHz Impedance - Lead Spacing 0.315" Dia (8.00mm) Height - Seated (Max) 0.402" (10.20mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount	Manufacturer Part Number	EEV-TG1V101UP	
Auminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesAutomotive, AEC-Q200, TGCapacitance100µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)500 mOhm @ 100kHzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature40°C ~ 125°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency128.1mA @ 120HzImpedance-Lead Spacing-Size / Dimension0.315° Dia (8.00mm)Height - Seated (Max)0.402° (10.20mm)Surface Mount Land Size0.327° L x 0.327° W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Manufacturer	Panasonic Electronic Components	
PackageRadial, Can - SMDSeriesAutomotive, AEC-Q200, TGCapacitance100µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)500 m/m @ 100kHzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency128.1mA @ 120HzImpedance-Lead Spacing-Size / Dimension0.315° Dia (8.00mm)Height - Seated (Max)0.327° L x 0.327° W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadia, Can - SMD	Category	Capacitors	
SeriesAutomotive, AEC-Q200, TGCapacitance100µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)500 mOhm @ 100kHzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature40°C ~ 125°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency197mA @ 100kHzImpedance-Size / Dimension0.315° Dia (8.00mm)Height - Seated (Max)0.402° (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSatial, Can - SMD		Aluminum Electrolytic Capacitors	
Capacitance100µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)500 mOhm @ 100kHzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency128.1mA @ 120HzImpedance-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRatial, Can - SMD	Package	Radial, Can - SMD	
Tolerance±0%Voltage - Rated35VESR (Equivalent Series Resistance)500 mOhm @ 100kHzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency128.1mA @ 120HzImpedance-Lead Spacing0.315" Dia (8.00mm)Size / Dimension0.402" (10.20mm)Height - Seated (Max)0.402" (10.20mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Series	Automotive, AEC-Q200, TG	
Voltage - Rated35VESR (Equivalent Series Resistance)500 mOhm @ 100kHzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency128.1mA @ 120HzInpedance-Lead Spacing0.315" Dia (8.00mm)Size / Dimension0.402" (10.20mm)Height - Seated (Max)0.402" (10.20mm)Mounting TypeSurface Mount Land SizePackage / CaseRatial, Can - SMD	Capacitance	100µF	
ESR (Equivalent Series Resistance)500 mOhm @ 100kHzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency128.1mA @ 120HzInpedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeRadial, Can - SMD	Tolerance	$\pm 20\%$	
Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency128.1mA @ 120HzRipple Current - High Frequency197mA @ 100kHzImpedance-Lead Spacing0.315" Dia (8.00mm)Size / Dimension0.402" (10.20mm)Height - Seated (Max)0.327" L x 0.327" W (8.30mm x 8.30mm)Surface Mount Land SizeSurface MountMounting TypeRadial, Can - SMD	Voltage - Rated	35V	
Operating Temperature-40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency128.1mA @ 120HzRipple Current - High Frequency197mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mouning TypeRadial, Can - SMD	ESR (Equivalent Series Resistance)	500 mOhm @ 100kHz	
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency128.1mA @ 120HzRipple Current - High Frequency197mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm) x 8.30mm) x 8.30mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSatial Can - SMD	Lifetime @ Temp.	2000 Hrs @ 125°C	
ApplicationsGeneral PurposeRipple Current - Low Frequency128.1mA @ 120HzRipple Current - High Frequency197mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Operating Temperature	-40°C ~ 125°C	
Ripple Current - Low Frequency128.1mA @ 120HzRipple Current - High Frequency197mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Polarization	Polar	
InInRipple Current - High Frequency197mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Applications	General Purpose	
Impedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Ripple Current - Low Frequency	128.1mA @ 120Hz	
Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Ripple Current - High Frequency	197mA @ 100kHz	
Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Impedance	-	
Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Lead Spacing	-	
Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Size / Dimension	0.315" Dia (8.00mm)	
Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Height - Seated (Max)	0.402" (10.20mm)	
Package / Case Radial, Can - SMD	Surface Mount Land Size	0.327" L x 0.327" W (8.30mm x 8.30mm)	
	Mounting Type	Surface Mount	
Papart array	Package / Case	Radial, Can - SMD	
Report errors			Report errors?

EEV-TG1V101UP Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

EEV-TG1V101UP Payment Methods



EEV-TG1V101UP Shipping Methods



If you have any question about EEV-TG1V101UP, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com