



EGG.0K.302.CYM Information

Heisener.com

Part Number EGG.0K.302.CYM

Manufacturer LEMO

Category Connectors, Interconnects

Circular Connectors

Description CONN PNL MNT RCPT 2SKT CRIMP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EGG.0K.302.CYM Specifications

Manufacturer Part Number EGG.0K.302.CYM Manufacturer LEMO Category Connectors, Interconnects Circular Connectors Package - Series 0K Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 302 Shell Size, MIL - Mounting Type Panel Mount, Flange - Rear Side Nut Termination Crimp Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 10A		
CategoryConnectors, InterconnectsPackage-Series0KConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypePanel Mount, Flange - Rear Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating10A	Manufacturer Part Number	EGG.0K.302.CYM
Package-Series0KConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypePanel Mount, Flange - Rear Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating10A	Manufacturer	LEMO
Package-Series0KConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypePanel Mount, Flange - Rear Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating10A	Category	Connectors, Interconnects
SeriesOKConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypePanel Mount, Flange - Rear Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating10A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypePanel Mount, Flange - Rear Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating10A	Package	-
Number of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypePanel Mount, Flange - Rear Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating10A	Series	0K
Shell Size - Insert 302 Shell Size, MIL - Mounting Type Panel Mount, Flange - Rear Side Nut Termination Crimp Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 10A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange - Rear Side Nut Termination Crimp Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 10A	Number of Positions	2
Mounting TypePanel Mount, Flange - Rear Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating10A	Shell Size - Insert	302
Termination Crimp Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 10A	Shell Size, MIL	-
Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 10A	Mounting Type	Panel Mount, Flange - Rear Side Nut
Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 10A	Termination	Crimp
Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 10A	Fastening Type	Push-Pull, Detent Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 10A	Orientation	G
Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 10A	Ingress Protection	IP66/68 - Dust Tight, Water Resistant, Waterproof
Features Shielded Voltage - Rated - Current Rating 10A	Shell Material, Finish	Brass, Chrome Plated
Voltage - Rated - Current Rating 10A	Contact Finish	Gold
Current Rating 10A	Features	Shielded
-	Voltage - Rated	-
Report errors?	Current Rating	10A
		Report errors?

EGG.0K.302.CYM Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EGG.0K.302.CYM Payment Methods



















EGG.0K.302.CYM Shipping Methods













If you have any question about EGG.0K.302.CYM, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com