



EGG.1K.306.CLL Information

Heisener.com

Part Number EGG.1K.306.CLL

Manufacturer LEMO

Category Connectors, Interconnects

Circular Connectors

Description CONN PNL MNT RCPT 6SKT SLD CUP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EGG.1K.306.CLL Specifications

Manufacturer Part Number EGG.I K. 306.CLL Manufacturer LEMO Category Connectors, Interconnects Package - Series IK Connector Type Receptacle, Female Sockets Number of Positions 6 Shell Size - Insert 306 Shell Size, MIL - Mounting Type Panel Mount, Flange - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7A		
CategoryConnectors, InterconnectsPackage-Series1 KConnector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - Insert306Shell Size, MIL-Mounting TypePanel Mount, Flange - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7A	Manufacturer Part Number	EGG.1K.306.CLL
Package-Series1KConnector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - Insert306Shell Size, MIL-Mounting TypePanel Mount, Flange - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7A	Manufacturer	LEMO
Package-Series1KConnector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - Insert306Shell Size, MIL-Mounting TypePanel Mount, Flange - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress Protection1P66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7A	Category	Connectors, Interconnects
Series1KConnector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - Insert306Shell Size, MIL-Mounting TypePanel Mount, Flange - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - Insert306Shell Size, MIL-Mounting TypePanel Mount, Flange - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7A	Package	-
Number of Positions6Shell Size - Insert306Shell Size, MIL-Mounting TypePanel Mount, Flange - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7A	Series	1K
Shell Size - Insert 306 Shell Size, MIL - Mounting Type Panel Mount, Flange - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7A	Number of Positions	6
Mounting TypePanel Mount, Flange - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7A	Shell Size - Insert	306
Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7A	Shell Size, MIL	-
Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7A	Mounting Type	Panel Mount, Flange - Rear Side Nut
Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7A	Termination	Solder Cup
Ingress Protection Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating TP66/68 - Dust Tight, Water Resistant, Waterproof Brass, Chrome Plated Gold Shielded - Current Rating	Fastening Type	Push-Pull, Detent Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7A	Orientation	G
Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7A	Ingress Protection	IP66/68 - Dust Tight, Water Resistant, Waterproof
Features Shielded Voltage - Rated - Current Rating 7A	Shell Material, Finish	Brass, Chrome Plated
Voltage - Rated - Current Rating 7A	Contact Finish	Gold
Current Rating 7A	Features	Shielded
-	Voltage - Rated	-
Report errors?	Current Rating	7A
		Report errors?

EGG.1K.306.CLL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EGG.1K.306.CLL Payment Methods



















EGG.1K.306.CLL Shipping Methods













If you have any question about EGG.1K.306.CLL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com