



EGG.2K.306.CLL Information

Heisener.com

Part Number EGG.2K.306.CLL

Manufacturer LEMO

Category Connectors, Interconnects

Circular Connectors

Description CONN PNL MNT RCPT 6SKT SLD CUP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EGG.2K.306.CLL Specifications

Manufacturer Part Number EGG.2K.306.CLL Manufacturer LEMO Category Connectors, Interconnects Package - Series 2K Connector Type Receptacle, Female Sockets Number of Positions 6 Shell Size - Insert 306 Shell Size, MIL - Mounting Type Panel Mount, Flange - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 12A		
Category Circular Connectors Package - Series 2K Connector Type Receptacle, Female Sockets Number of Positions 6 Shell Size - Insert 306 Shell Size, MIL - Mounting Type Panel Mount, Flange - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Voltage - Rated Voltage - Rated Current Rating 12A	Manufacturer Part Number	EGG.2K.306.CLL
Package-Series2KConnector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - Insert306Shell Size, MIL-Mounting TypePanel Mount, Flange - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating12A	Manufacturer	LEMO
Package-Series2KConnector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - Insert306Shell Size, MIL-Mounting TypePanel Mount, Flange - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating12A	Category	Connectors, Interconnects
Series 2K Connector Type Receptacle, Female Sockets Number of Positions 6 Shell Size - Insert 306 Shell Size, MIL - Mounting Type Panel Mount, Flange - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 12A		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 6 Shell Size - Insert 306 Shell Size, MIL - Mounting Type Panel Mount, Flange - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 12A	Package	-
Number of Positions6Shell Size - Insert306Shell Size, MIL-Mounting TypePanel Mount, Flange - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating12A	Series	2K
Shell Size - Insert 306 Shell Size, MIL - Mounting Type Panel Mount, Flange - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 12A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 12A	Number of Positions	6
Mounting TypePanel Mount, Flange - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating12A	Shell Size - Insert	306
Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 12A	Shell Size, MIL	-
Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 12A	Mounting Type	Panel Mount, Flange - Rear Side Nut
Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 12A	Termination	Solder Cup
Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 12A	Fastening Type	Push-Pull, Detent Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 12A	Orientation	G
Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 12A	Ingress Protection	IP66/68 - Dust Tight, Water Resistant, Waterproof
Features Shielded Voltage - Rated - Current Rating 12A	Shell Material, Finish	Brass, Chrome Plated
Voltage - Rated - Current Rating 12A	Contact Finish	Gold
Current Rating 12A	Features	Shielded
-	Voltage - Rated	-
Report errors?	Current Rating	12A
		Report errors?

EGG.2K.306.CLL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EGG.2K.306.CLL Payment Methods



















EGG.2K.306.CLL Shipping Methods













If you have any question about EGG.2K.306.CLL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com