



### EGL.2K.304.CLA Information

Heisener.com

Part Number EGL.2K.304.CLA

Manufacturer LEMO

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PNL MNT RCPT 4PIN SLD CUP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# EGL.2K.304.CLA Specifications

| Manufacturer Part Number       EGL.2K.304.CLA         Manufacturer       LEMO         Category       Connectors, Interconnects         Package       -         Series       2K         Connector Type       Receptacle, Male Pins         Number of Positions       4         Shell Size - Insert       304         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange - Rear Side Nut         Termination       Solder Cup         Fastening Type       Push-Pull, Detent Lock         Orientation       L         Ingress Protection       IP66/68 - Dust Tight, Water Resistant, Waterproof         Shell Material, Finish       Brass, Chrome Plated         Contact Finish       Gold         Features       Shielded         Voltage - Rated       -         Current Rating       15A |                          |   |
|--|--------------------------|---|
| CategoryConnectors, InterconnectsPackage-Series2KConnector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert304Shell Size, MIL-Mounting TypePanel Mount, Flange - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationLIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating15A  | Manufacturer Part Number | EGL.2K.304.CLA                                    |
| Package-Series2KConnector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert304Shell Size, MIL-Mounting TypePanel Mount, Flange - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationLIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating15A   | Manufacturer             | LEMO  |
| Package-Series2KConnector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert304Shell Size, MIL-Mounting TypePanel Mount, Flange - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationLIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating15A   | Category                 | Connectors, Interconnects                         |
| Series 2K Connector Type Receptacle, Male Pins Number of Positions 4 Shell Size - Insert 304 Shell Size, MIL - Mounting Type Panel Mount, Flange - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation L Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 15A  |                          | Circular Connectors                               |
| Connector Type Receptacle, Male Pins  Number of Positions 4  Shell Size - Insert 304  Shell Size, MIL -  Mounting Type Panel Mount, Flange - Rear Side Nut  Termination Solder Cup  Fastening Type Push-Pull, Detent Lock  Orientation L  Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof  Shell Material, Finish Brass, Chrome Plated  Contact Finish Gold  Features Shielded  Voltage - Rated  Current Rating 15A   | Package                  | -   |
| Number of Positions4Shell Size - Insert304Shell Size, MIL-Mounting TypePanel Mount, Flange - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationLIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating15A  | Series                   | 2K  |
| Shell Size - Insert304Shell Size, MIL-Mounting TypePanel Mount, Flange - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationLIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating15A  | Connector Type           | Receptacle, Male Pins                             |
| Shell Size, MIL  Mounting Type Panel Mount, Flange - Rear Side Nut  Termination Solder Cup  Fastening Type Push-Pull, Detent Lock  Orientation L  Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof  Shell Material, Finish Brass, Chrome Plated  Contact Finish Gold  Features Shielded  Voltage - Rated -  Current Rating 15A   | Number of Positions      | 4   |
| Mounting TypePanel Mount, Flange - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationLIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating15A  | Shell Size - Insert      | 304   |
| Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation L Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 15A   | Shell Size, MIL          | -   |
| Fastening Type Push-Pull, Detent Lock Orientation L Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 15A  | Mounting Type            | Panel Mount, Flange - Rear Side Nut               |
| Orientation L Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 15A  | Termination              | Solder Cup  |
| Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 15A  | Fastening Type           | Push-Pull, Detent Lock                            |
| Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 15A  | Orientation              | L   |
| Contact Finish Gold Features Shielded  Voltage - Rated - Current Rating 15A  | Ingress Protection       | IP66/68 - Dust Tight, Water Resistant, Waterproof |
| Features Shielded  Voltage - Rated - Current Rating 15A  | Shell Material, Finish   | Brass, Chrome Plated                              |
| Voltage - Rated - Current Rating 15A   | Contact Finish           | Gold  |
| Current Rating 15A   | Features                 | Shielded  |
| -  | Voltage - Rated          | -   |
| Report errors?   | Current Rating           | 15A   |
|  |                          | Report errors?                                    |

#### EGL.2K.304.CLA Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **EGL.2K.304.CLA Payment Methods**



















## EGL.2K.304.CLA Shipping Methods













If you have any question about EGL.2K.304.CLA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com