

EGM10DTMS-S189

EGM10DTMS-S189 Information

| Heisener.com | EGM10DTMS-S189 Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 20POS 0.156 - For the pricing/inventory/lead time, please contact | |
|--------------------|---|-----------------|
| For Reference Only | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



EGM10DTMS-S189 Specifications

| ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions/Bay/Row0062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeSolderContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness10Contact TypeGoldContact TypeIop BellowsContact TypeSoldersensensensensensensensensensensensensens | | | |
|---|-----------------------------|---|----------------|
| CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions/Bay/Row00Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish Thickness0.04Contact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsContact TypeBueColorBueFaque FeatureSide MountOpening, Unthreaded, 0.125" (3.18mm) DiaCoperating Temperature-65°C ~ 125°C | Manufacturer Part Number | EGM10DTMS-S189 | |
| Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 10 Number of Positions 20 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Contact Material Polosphor Bronze Contact Finish Gold Contact Type Loop Bellows Color Blue Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C | Manufacturer | Sullins Connector Solutions | |
| Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C | Category | Connectors, Interconnects | |
| Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions/Bay/Row20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlueColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C | | Card Edge Connectors - Edgeboard Connectors | |
| Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact Finish ThicknessJopin BionzeContact TypeLoop BellowsColorBueFlange FeatureSideMount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C | Package | - | |
| GenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact TypeLoop BellowsColorBlueFaquee FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C | Series | - | |
| Number of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact TypeIopin (0.25µm)Contact TypeLoop BellowsColorBlueFaquere FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C | Card Type | Non Specified - Dual Edge | |
| Number of Positions 20 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Mounting Type Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Type Loop Bellows Color Blue Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C | Gender | Female | |
| Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C | Number of Positions/Bay/Row | 10 | |
| Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C | Number of Positions | 20 | |
| Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlueColorSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C | Card Thickness | 0.062" (1.57mm) | |
| Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessI0µin (0.25µm)Contact TypeLoop BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C | Number of Rows | 2 | |
| Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C | Pitch | 0.156" (3.96mm) | |
| TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C | Features | - | |
| Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C | Mounting Type | Through Hole, Right Angle | |
| Contact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C | Termination | Solder | |
| Contact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C | Contact Material | Phosphor Bronze | |
| Contact TypeLoop BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C | Contact Finish | Gold | |
| ColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C | Contact Finish Thickness | 10µin (0.25µm) | |
| Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C | Contact Type | Loop Bellows | |
| Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$ | Color | Blue | |
| | Flange Feature | Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia | |
| Report errors? | Operating Temperature | -65°C ~ 125°C | |
| Report chois. | | | Report errors? |

EGM10DTMS-S189 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

EGM10DTMS-S189 Payment Methods





If you have any question about EGM10DTMS-S189, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com