

**EHT-120-01-S-D-SM-LC-30-K Information**


For Reference Only

**Part Number** [EHT-120-01-S-D-SM-LC-30-K](#)  
**Manufacturer** Samtec Inc.  
**Category** Connectors, Interconnects  
[Rectangular Connectors - Headers, Male Pins](#)  
**Description** 2MM EJECTOR HEADER  
**Package** -  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)



[Request a Quote](#)

**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**EHT-120-01-S-D-SM-LC-30-K Specifications**

|                            |  |
|----------------------------|--|
| Manufacturer Part Number   | <a href="#">EHT-120-01-S-D-SM-LC-30-K</a>  |
| Manufacturer               | Samtec Inc.  |
| Category                   | Connectors, Interconnects<br><a href="#">Rectangular Connectors - Headers, Male Pins</a> |
| Package                    | -  |
| Series                     | EHT  |
| Connector Type             | Header   |
| Contact Type               | Male Pin   |
| Pitch - Mating             | 0.079" (2.00mm)  |
| Style                      | Board to Cable/Wire  |
| Shrouding                  | Shrouded - 4 Wall  |
| Number of Positions        | 40   |
| Number of Positions Loaded | 39   |
| Number of Rows             | 2  |
| Row Spacing - Mating       | 0.079" (2.00mm)  |
| Mounting Type              | Surface Mount  |
| Termination                | Solder   |
| Fastening Type             | Latch Lock/Eject Hooks   |
| Contact Length - Mating    | 0.120" (3.05mm)  |
| Contact Length - Post      | -  |
| Overall Contact Length     | -  |
| Insulation Height          | 0.370" (9.40mm)  |
| Contact Shape              | Square   |
| Contact Finish - Mating    | Gold   |

|                                   |   |
|-----------------------------------|---|
| Contact Finish Thickness - Mating | 30μin (0.76μm)                          |
| Contact Finish - Post             | Tin                                     |
| Contact Material                  | Phosphor Bronze                         |
| Insulation Material               | Liquid Crystal Polymer (LCP)            |
| Features                          | Board Lock, Keying Slot, Pick and Place |
| Operating Temperature             | -55°C ~ 125°C                           |
| Ingress Protection                | -                                       |
| Material Flammability Rating      | UL94 V-0                                |
| Insulation Color                  | Black                                   |
|                                   | <a href="#">Report errors?</a>          |

## EHT-120-01-S-D-SM-LC-30-K Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## EHT-120-01-S-D-SM-LC-30-K Payment Methods



## EHT-120-01-S-D-SM-LC-30-K Shipping Methods



If you have any question about EHT-120-01-S-D-SM-LC-30-K, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)