

# EKMQ630ELL472MP50S

### EKMQ630ELL472MP50S Information



For Reference Only

Part Number EKMQ630ELL472MP50S

Manufacturer United Chemi-Con

**Category** Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 4700UF 20% 63V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## EKMQ630ELL472MP50S Specifications

Manufacturer Part Number         EKMQ630ELL472MP50S           Manufacturer         United Chemi-Con           Category         Capacitors           Package         Radial, Can           Series         KMQ           Capacitance         4700µF           Tolerance         ±20%           Voltage - Rated         63V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         General Purpose           Ripple Current - Low Frequency         2.45A @ 120Hz           Ripple Current - High Frequency         2.646A @ 100kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         0.866" Dia (22.00mm)           Height - Seated (Max)         2.047" (52.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		
CategoryCapacitorsPackageRadial, CanSeriesKMQCapacitance4700µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.45A @ 120HzRipple Current - High Frequency2.646A @ 100kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	EKMQ630ELL472MP50S
Package Radial, Can  Series KMQ  Capacitance 4700µF  Tolerance ±20%  Voltage - Rated 63V  ESR (Equivalent Series Resistance) -  Lifetime @ Temp. 2000 Hrs @ 105°C  Operating Temperature -55°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.45A @ 120Hz  Ripple Current - High Frequency 2.646A @ 100kHz  Impedance -  Lead Spacing 0.394" (10.00mm)  Size / Dimension 0.866" Dia (22.00mm)  Height - Seated (Max) 2.047" (52.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Manufacturer	United Chemi-Con
Package         Radial, Can           Series         KMQ           Capacitance         4700µF           Tolerance         ±20%           Voltage - Rated         63V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.45A @ 120Hz           Ripple Current - High Frequency         2.646A @ 100kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         0.866" Dia (22.00mm)           Height - Seated (Max)         2.047" (52.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         KMQ           Capacitance         4700μF           Tolerance         ±20%           Voltage - Rated         63V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.45A @ 120Hz           Ripple Current - High Frequency         2.646A @ 100kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         0.866" Dia (22.00mm)           Height - Seated (Max)         2.047" (52.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance         4700µF           Tolerance         ±20%           Voltage - Rated         63V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.45A @ 120Hz           Ripple Current - High Frequency         2.646A @ 100kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         0.866" Dia (22.00mm)           Height - Seated (Max)         2.047" (52.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 63V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C  Operating Temperature -55°C ~ 105°C  Polarization Polar  Applications General Purpose Ripple Current - Low Frequency 2.45A @ 120Hz Ripple Current - High Frequency 2.646A @ 100kHz  Impedance - Lead Spacing 0.394" (10.00mm)  Size / Dimension 0.866" Dia (22.00mm)  Height - Seated (Max) 2.047" (52.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Series	KMQ
Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.45A @ 120HzRipple Current - High Frequency2.646A @ 100kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	4700μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 105°C  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  2.45A @ 120Hz  Ripple Current - High Frequency  2.646A @ 100kHz  Impedance  - Lead Spacing  0.394" (10.00mm)  Size / Dimension  0.866" Dia (22.00mm)  Height - Seated (Max)  2.047" (52.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  2.45A @ 120Hz  Ripple Current - High Frequency  2.646A @ 100kHz  Impedance  Lead Spacing  0.394" (10.00mm)  Size / Dimension  0.866" Dia (22.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Voltage - Rated	63V
Operating Temperature  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  2.45A @ 120Hz  Ripple Current - High Frequency  2.646A @ 100kHz  Impedance  Lead Spacing  0.394" (10.00mm)  Size / Dimension  0.866" Dia (22.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.45A @ 120Hz Ripple Current - High Frequency 2.646A @ 100kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications  Ripple Current - Low Frequency  2.45A @ 120Hz  Ripple Current - High Frequency  2.646A @ 100kHz  Impedance  - Lead Spacing  0.394" (10.00mm)  Size / Dimension  0.866" Dia (22.00mm)  Height - Seated (Max)  2.047" (52.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  2.646A @ 100kHz  Impedance  - Lead Spacing  0.394" (10.00mm)  Size / Dimension  0.866" Dia (22.00mm)  Height - Seated (Max)  2.047" (52.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Polarization	Polar
Ripple Current - High Frequency  Impedance - Lead Spacing 0.394" (10.00mm)  Size / Dimension 0.866" Dia (22.00mm)  Height - Seated (Max) 2.047" (52.00mm)  Surface Mount Land Size - Mounting Type Through Hole  Package / Case Radial, Can	Applications	General Purpose
Impedance - Case	Ripple Current - Low Frequency	2.45A @ 120Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	2.646A @ 100kHz
Size / Dimension 0.866" Dia (22.00mm)  Height - Seated (Max) 2.047" (52.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size -  Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.866" Dia (22.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	2.047" (52.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

### EKMQ630ELL472MP50S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### EKMQ630ELL472MP50S Payment Methods





















### EKMQ630ELL472MP50S Shipping Methods













If you have any question about EKMQ630ELL472MP50S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com