

EKXJ221ELL121MK30S

EKXJ221ELL121MK30S Information



For Reference Only

Part Number EKXJ221ELL121MK30S

Manufacturer United Chemi-Con

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 120UF 20% 220V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EKXJ221ELL121MK30S Specifications

Manufacturer Part Number EKXJ221ELL121MK30S Manufacturer United Chemi-Con Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series KXJ Capacitance 120μF Tolerance ±20% Voltage - Rated 220V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 725mA @ 120Hz Ripple Current - High Frequency 1.63125A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.240" (31.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	*	
Category Capacitors Package Radial, Can Series KXJ Capacitance 120µF Tolerance ±20% Voltage - Rated 220V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 725mA @ 120Hz Ripple Current - High Frequency 1.63125A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.240" (31.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	EKXJ221ELL121MK30S
Package Radial, Can Series KXJ Capacitance 120µF Tolerance ±20% Voltage - Rated 220V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 725mA @ 120Hz Ripple Current - High Frequency 1.63125A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.240" (31.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	United Chemi-Con
Package Radial, Can Series KXJ Capacitance 120μF Tolerance ±20% Voltage - Rated 220V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 725mA @ 120Hz Ripple Current - High Frequency 1.63125A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.240" (31.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series KXJ Capacitance 120μF Tolerance ±20% Voltage - Rated 220V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 725mA @ 120Hz Ripple Current - High Frequency 1.63125A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.240" (31.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 120µF Tolerance ±20% Voltage - Rated 220V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 725mA @ 120Hz Ripple Current - High Frequency 1.63125A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.240" (31.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 220V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 725mA @ 120Hz Ripple Current - High Frequency 1.63125A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.240" (31.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	KXJ
Voltage - Rated220VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency725mA @ 120HzRipple Current - High Frequency1.63125A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	120μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency 1.63125A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.240" (31.50mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency 1.63125A @ 120Hz Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 12000 Hrs @ 105°C -40°C ~	Voltage - Rated	220V
Operating Temperature -40°C ~ 105°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency 1.63125A @ 100kHz Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications Automotive Ripple Current - Low Frequency 725mA @ 120Hz Ripple Current - High Frequency 1.63125A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.240" (31.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	12000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 1.63125A @ 100kHz Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Automotive Automotive 725mA @ 120Hz 1.63125A @ 100kHz 1.63125A	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 1.63125A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.240" (31.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.240" (31.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	Automotive
Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.240" (31.50mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	725mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	1.63125A @ 100kHz
Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.240" (31.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.240" (31.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
Report errors.		Report errors?

EKXJ221ELL121MK30S Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EKXJ221ELL121MK30S Payment Methods





















EKXJ221ELL121MK30S Shipping Methods













If you have any question about EKXJ221ELL121MK30S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com