

EKXJ451ELL220MJ35S

EKXJ451ELL220MJ35S Information



For Reference Only

Part Number EKXJ451ELL220MJ35S

Manufacturer United Chemi-Con

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 22UF 20% 450V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EKXJ451ELL220MJ35S Specifications

Manufacturer Part Number EKXJ451ELL220MJ35S Manufacturer United Chemi-Con Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series KXJ Capacitance 22µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 250mA @ 120Hz Ripple Current - High Frequency 625mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 1.437" (36.50mm) Surface Mount Land Size -	*	
Category Capacitors Package Radial, Can Series KXJ Capacitance 22µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 250mA @ 120Hz Ripple Current - High Frequency 625mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 1.437" (36.50mm) Surface Mount Land Size -	Manufacturer Part Number	EKXJ451ELL220MJ35S
PackageRadial, CanSeriesKXJCapacitance22µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency250mA @ 120HzRipple Current - High Frequency625mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.437" (36.50mm)Surface Mount Land Size-	Manufacturer	United Chemi-Con
PackageRadial, CanSeriesKXJCapacitance22μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency250mA @ 120HzRipple Current - High Frequency625mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.437" (36.50mm)Surface Mount Land Size-	Category	Capacitors
Series KXJ Capacitance 22μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105 °C Operating Temperature -25 °C ~ 105 °C Polarization Polar Applications Automotive Ripple Current - Low Frequency 250mA @ 120Hz Ripple Current - High Frequency 625mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 1.437" (36.50mm) Surface Mount Land Size -		Aluminum Electrolytic Capacitors
Capacitance $22\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $450V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $12000 \text{ Hrs } @ 105^{\circ}\text{C}$ Operating Temperature $-25^{\circ}\text{C} \sim 105^{\circ}\text{C}$ PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency $250\text{mA} @ 120\text{Hz}$ Ripple Current - High Frequency $625\text{mA} @ 100\text{kHz}$ Impedance-Lead Spacing $0.197'' (5.00\text{mm})$ Size / Dimension $0.394''$ Dia (10.00mm)Height - Seated (Max) $1.437'' (36.50\text{mm})$ Surface Mount Land Size-	Package	Radial, Can
Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 250mA @ 120Hz Ripple Current - High Frequency 625mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 1.437" (36.50mm) Surface Mount Land Size -	Series	KXJ
Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 250mA @ 120Hz Ripple Current - High Frequency 625mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 1.437" (36.50mm) Surface Mount Land Size -	Capacitance	22μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency 625mA @ 120Hz Ripple Current - High Frequency 12000 Hrs @ 105°C Automotive 250mA @ 120Hz 250mA @ 120Hz 250mA @ 100kHz	Tolerance	±20%
Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 250mA @ 120Hz Ripple Current - High Frequency 625mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 1.437" (36.50mm) Surface Mount Land Size -	Voltage - Rated	450V
Operating Temperature -25°C ~ 105°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency 625mA @ 120Hz Rippedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) Surface Mount Land Size - -	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications Automotive Ripple Current - Low Frequency 250mA @ 120Hz Ripple Current - High Frequency 625mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 1.437" (36.50mm) Surface Mount Land Size -	Lifetime @ Temp.	12000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 625mA @ 120Hz 625mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 1.437" (36.50mm) Surface Mount Land Size -	Operating Temperature	-25°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 625mA @ 120Hz 625mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 1.437" (36.50mm) Surface Mount Land Size -	Polarization	Polar
Ripple Current - High Frequency 625mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 1.437" (36.50mm) Surface Mount Land Size -	Applications	Automotive
Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 1.437" (36.50mm) Surface Mount Land Size -	Ripple Current - Low Frequency	250mA @ 120Hz
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 1.437" (36.50mm) Surface Mount Land Size -	Ripple Current - High Frequency	625mA @ 100kHz
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.437" (36.50mm)Surface Mount Land Size-	Impedance	-
Height - Seated (Max) Surface Mount Land Size 1.437" (36.50mm) -	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size -	Size / Dimension	0.394" Dia (10.00mm)
	Height - Seated (Max)	1.437" (36.50mm)
	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

EKXJ451ELL220MJ35S Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EKXJ451ELL220MJ35S Payment Methods



















EKXJ451ELL220MJ35S Shipping Methods













If you have any question about EKXJ451ELL220MJ35S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com