

# EMC17DRXH

#### **EMC17DRXH** Information

Heisener.com	Part Number Manufacturer Category Description Package	EMC17DRXH Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 34POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **EMC17DRXH Specifications**

ManufacturerSullins Connector SolutionsCategoryConnectors, Edgeboard ConnectorsPackage-Package-Series-Card TypeMon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row17Number of Positions/Bay/Row062° (1.57mm)Number of Rows0.602° (1.57mm)Number of Rows0.100° (2.54mm)Features0.100° (2.54mm)Features0.100° (2.54mm)Contact MaterialSolderContact FinishSolderContact FinishGoldContact FinishGoldContact TypeSile NongenseContact TypeSile No		
CatagoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row17Number of Positions/Bay/Row062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Features-Features-Mounting TypeOiderContact MaterialSolderContact Finish Thickness0jui (0.76µm)Contact Finish ThicknessSolin (0.76µm)Contact TypeFull BellowsContact TypeSupin (0.76µm)Contact TypeSupin (0.76µm)Contact TypeSupin (0.76µm)Colare Tinish ThicknessSupin (0.76µm)Colare TypeSupin (0.125° (0.18µm)Contact Type-Sc° <0.25°C	Manufacturer Part Number	EMC17DRXH
Card Edge Connectors - Edgeboard Connectors       Package     -       Series     -       Card Type     Non Specified - Dual Edge       Gender     Female       Number of Positions/Bay/Row     17       Number of Positions     34       Card Thickness     0.062" (1.57mm)       Number of Rows     2       Pitch     0.100" (2.54mm)       Mounting Type     -       Mounting Type     Through Hole       Contact Material     Solder       Contact Material     Gold       Contact Finish Thickness     30µin (0.76µm)       Contact Type     Full Bellows       Color     Blue       Flange Feature     Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia       Operating Temperature     -65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row17Number of Positions34Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Mounting Type-Mounting TypeOilor (2.54mm)Contact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row17Number of Positions/Bay/Row34Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFul BellowsColorBlueFlange Feature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row17Number of Positions34Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessSipin (0.76µm)Contact TypeFull BellowsColorBueColorSolderColorSolderColorSolderContact TypeSolderColorSolderC	Package	-
GenderFemaleNumber of Positions/Bay/Row17Number of Positions34Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-55°C ~ 125°C	Series	-
Number of Positions/Bay/Row17Number of Positions34Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFage FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions     34       Card Thickness     0.062" (1.57mm)       Number of Rows     2       Pitch     0.100" (2.54mm)       Features     -       Mounting Type     Through Hole       Contact Material     Solder       Contact Finish     Gold       Contact Finish Thickness     30µin (0.76µm)       Contact Type     Full Bellows       Color     Blue       Flange Feature     Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia       Operating Temperature     -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	17
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	34
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold
Color Blue   Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia   Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Blue
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	$-65^{\circ}C \sim 125^{\circ}C$
		Report errors?

#### **EMC17DRXH Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **EMC17DRXH Payment Methods**



### **EMC17DRXH Shipping Methods**



If you have any question about EMC17DRXH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com