

# EMC65DRTS-S93

est a Quote

## **EMC65DRTS-S93 Information**

Heisener.com	Part Number	EMC65DRTS-S93	
	Manufacturer	Sullins Connector Solutions	
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	
	Description	CONN EDGE DUAL FMALE 130POS .100	
	Package	-	
		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **EMC65DRTS-S93 Specifications**

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Card Edge Connectors - Edgeboard ConnectorsSeries-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row65Number of Positions/Bay/Row0.093" (2.36mm)Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact FinishGoldContact Finish ThicknessGoldContact TypeFul BellowsContact TypeSull BellowsColorBueFaque FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaCoperating Temperature-65°C ~ 125°C			
CatagoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row65Number of Positions0.093° (2.36mm)Card Thickness0.093° (2.36mm)Number of Rows2Pitch0.100° (2.54mm)Features-Mounting TypeForogh HoleContact MaterialSolderContact Finish Thickness0.001 (0.76µm)Contact TypeFull BellowsContact TypeSupin (0.76µm)Contact TypeSupin (0.76µm)Contact TypeSupin (0.76µm)Contact TypeSupin (0.76µm)Contact TypeSupin (0.76µm)ColorBueFlange FeatureSide Mount Opening, Unthreaded, 0.125° (3.18mm) DiaOperating Temperature-55°C ~125°C	Manufacturer Part Number	EMC65DRTS-S93	
AndCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row65Number of Positions130Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row65Number of Positions130Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Mounting Type-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaFlange Feature-65°C ~ 125°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row65Number of Positions130Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact FinishSolderContact Finish Thickness30µin (0.76µm)Contact TypeFul BellowsContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row65Number of Positions130Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact TypeFull BellowsContact TypeSuper SolutionsColorBueFaquere FeaturesSide SolutionsColorSolut Contact SolutionsColorSolut Contact SolutionsColorSolut Contact SolutionsColorSide SolutionsColorSolut Contact SolutionsFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row65Number of Positions130Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact TypeGuldContact TypeSupin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-	
Number of Positions/Bay/Row65Number of Positions130Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions 130   Card Thickness 0.093" (2.36mm)   Number of Rows 2   Pitch 0.100" (2.54mm)   Features -   Mounting Type Through Hole   Mounting Type Solder   Contact Material Gold   Contact Finish Gold   Contact Type Full Bellows   Color Blue   Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia   Operating Temperature -65°C ~ 125°C	Gender	Female	
Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	65	
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	130	
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.093" (2.36mm)	
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2	
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)	
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole	
Contact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder	
Contact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold	
ColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)	
Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Full Bellows	
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Blue	
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
	Operating Temperature	-65°C ~ 125°C	
		Report errors?	

#### **EMC65DRTS-S93** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **EMC65DRTS-S93 Payment Methods**





If you have any question about EMC65DRTS-S93, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com