

EMMA050400-P5RP-IC

EMMA050400-P5RP-IC Information



For Reference Only

Part Number EMMA050400-P5RP-IC

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 5V 30W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EMMA050400-P5RP-IC Specifications

Manufacturer Part Number EMMA050400-P5RP-IC Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Package - Series EMMA 30W Region Utilized International Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series EMMA 30W Region Utilized International Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Manufacturer Part Number	EMMA050400-P5RP-IC
AC DC Desktop, Wall Adapters Package - Series EMMA 30W Region Utilized International Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension AC DC Desktop, Wall Adapters EMMA 30W Multi-Blade (Included) Voltage - Output 90 ~ 264 VAC Voltage - Output 90 ~ 264 VAC AA AB Voltage - Output AB Voltage -	Manufacturer	CUI Inc.
Package - Series EMMA 30W Region Utilized International Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesEMMA 30WRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Included)Voltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)4APower (Watts)20WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormWall MountInput TypeMulti-Blade (Included)Voltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)4APower (Watts)20WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Package	-
Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Series	EMMA 30W
Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Region Utilized	International
Voltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)4APower (Watts)20WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Form	Wall Mount
Voltage - Output (Max) 4A Power (Watts) 20W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Input Type	Multi-Blade (Included)
Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 20W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Voltage - Output	5V
No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Current - Output (Max)	4A
Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Power (Watts)	20W
Applications Medical Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.28^{\circ}\text{L} \times 2.44^{\circ}\text{W} \times 1.45^{\circ}\text{H} (108.7\text{mm} \times 62.0\text{mm} \times 36.7\text{mm})$	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.28^{\circ}\text{L} \times 2.44^{\circ}\text{W} \times 1.45^{\circ}\text{H} (108.7\text{mm} \times 62.0\text{mm} \times 36.7\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.28^{\circ}\text{L} \times 2.44^{\circ}\text{W} \times 1.45^{\circ}\text{H} (108.7\text{mm} \times 62.0\text{mm} \times 36.7\text{mm})$	Applications	Medical
Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Efficiency	Level V
Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Operating Temperature	$0^{\circ}\text{C} \sim 40^{\circ}\text{C}$
	Output Connector	Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)
		Report errors?

EMMA050400-P5RP-IC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EMMA050400-P5RP-IC Payment Methods



















EMMA050400-P5RP-IC Shipping Methods













If you have any question about EMMA050400-P5RP-IC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com