

EMMA120250-P5RP-IC

EMMA120250-P5RP-IC Information



For Reference Only

Part Number EMMA120250-P5RP-IC

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 12V 30W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EMMA120250-P5RP-IC Specifications

Manufacturer Part Number EMMA120250-P5RP-IC Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Package - Series EMMA 30W Region Utilized International Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series EMMA 30W Region Utilized International Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Manufacturer Part Number	EMMA120250-P5RP-IC
Package-SeriesEMMA 30WRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Included)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)2.5APower (Watts)30WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Manufacturer	CUI Inc.
Package - Series EMMA 30W Region Utilized International Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesEMMA 30WRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Included)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)2.5APower (Watts)30WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Package	-
Form Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Uevel V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Series	EMMA 30W
Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28° L x 2.44° W x 1.45° H (108.7mm x 62.0mm x 36.7mm)	Form	Wall Mount
Voltage - Output Current - Output (Max) 2.5A Power (Watts) No Load Power Consumption Polarization Polarization Applications Efficiency Operating Temperature O°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Input Type	Multi-Blade (Included)
Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $30W$ No Load Power Consumption $300mW$ (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug R/A, $2.1mm$ I.D. x $5.5mm$ O.D. x $9.5mm$ Size / Dimension 4.28 " L x 2.44 " W x 1.45 " H ($108.7mm$ x $62.0mm$ x $36.7mm$)	Voltage - Output	12V
No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Current - Output (Max)	2.5A
Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.28^{\circ}\text{L} \times 2.44^{\circ}\text{W} \times 1.45^{\circ}\text{H} (108.7\text{mm} \times 62.0\text{mm} \times 36.7\text{mm})$	Power (Watts)	30W
Applications Medical Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.28^{\circ}\text{L} \times 2.44^{\circ}\text{W} \times 1.45^{\circ}\text{H} (108.7\text{mm} \times 62.0\text{mm} \times 36.7\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.28^{\circ}\text{L} \times 2.44^{\circ}\text{W} \times 1.45^{\circ}\text{H} (108.7\text{mm} \times 62.0\text{mm} \times 36.7\text{mm})$	Applications	Medical
Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Efficiency	Level V
Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)
		Report errors?

EMMA120250-P5RP-IC Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EMMA120250-P5RP-IC Payment Methods



















EMMA120250-P5RP-IC Shipping Methods













If you have any question about EMMA120250-P5RP-IC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com