

# **EMMA150200-P6P-IC**

#### EMMA150200-P6P-IC Information



For Reference Only

Part Number EMMA150200-P6P-IC

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC WALL MOUNT ADAPTER 15V 30W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## EMMA150200-P6P-IC Specifications

Manufacturer Part Number         EMMA150200-P6P-IC           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           Package         -           Series         EMMA 30W           Region Utilized         International           Form         Wall Mount           Input Type         Multi-Blade (Included)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         15V           Current - Output (Max)         2A           Power (Watts)         30W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         Medical           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         EMMA 30W           Region Utilized         International           Form         Wall Mount           Input Type         Multi-Blade (Included)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         15V           Current - Output (Max)         2A           Power (Watts)         30W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         Medical           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Manufacturer Part Number	EMMA150200-P6P-IC
Package         -           Series         EMMA 30W           Region Utilized         International           Form         Wall Mount           Input Type         Multi-Blade (Included)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         15 V           Current - Output (Max)         2A           Power (Watts)         30W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         Medical           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Manufacturer	CUI Inc.
Package         -           Series         EMMA 30W           Region Utilized         International           Form         Wall Mount           Input Type         Multi-Blade (Included)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         15V           Current - Output (Max)         2A           Power (Watts)         30W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         Medical           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesEMMA 30WRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Included)Voltage - Input90 ~ 264 VACVoltage - Output15VCurrent - Output (Max)2APower (Watts)30WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormWall MountInput TypeMulti-Blade (Included)Voltage - Input90 ~ 264 VACVoltage - Output15VCurrent - Output (Max)2APower (Watts)30WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Package	-
Form Wall Mount Input Type Multi-Blade (Included)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 15V  Current - Output (Max) 2A  Power (Watts) 30W  No Load Power Consumption 300mW (Max)  Polarization Positive Center  Applications Medical  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Series	EMMA 30W
Input Type Multi-Blade (Included)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 15V  Current - Output (Max) 2A  Power (Watts) 30W  No Load Power Consumption 300mW (Max)  Polarization Positive Center  Applications Medical  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Region Utilized	International
Voltage - Input  90 ~ 264 VAC  Voltage - Output  15V  Current - Output (Max)  2A  Power (Watts)  No Load Power Consumption  300mW (Max)  Polarization  Positive Center  Applications  Medical  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Form	Wall Mount
Voltage - Output  Current - Output (Max)  2A  Power (Watts)  30W  No Load Power Consumption  Polarization  Polarization  Applications  Efficiency  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Input Type	Multi-Blade (Included)
Current - Output (Max)  2A  Power (Watts)  30W  No Load Power Consumption  300mW (Max)  Polarization  Positive Center  Applications  Medical  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts)  No Load Power Consumption  300mW (Max)  Polarization  Applications  Medical  Efficiency  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Voltage - Output	15V
No Load Power Consumption 300mW (Max)  Polarization Positive Center  Applications Medical  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Current - Output (Max)	2A
Polarization Positive Center  Applications Medical  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $4.28^{\circ}\text{L} \times 2.44^{\circ}\text{W} \times 1.45^{\circ}\text{H} (108.7\text{mm} \times 62.0\text{mm} \times 36.7\text{mm})$	Power (Watts)	30W
Applications Medical Efficiency Level V   Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm   Size / Dimension $4.28^{\circ}\text{L} \times 2.44^{\circ}\text{W} \times 1.45^{\circ}\text{H} (108.7\text{mm} \times 62.0\text{mm} \times 36.7\text{mm})$	No Load Power Consumption	300mW (Max)
Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $4.28^{\circ}\text{L} \times 2.44^{\circ}\text{W} \times 1.45^{\circ}\text{H} (108.7\text{mm} \times 62.0\text{mm} \times 36.7\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.28^{\circ}\text{L} \times 2.44^{\circ}\text{W} \times 1.45^{\circ}\text{H} (108.7\text{mm} \times 62.0\text{mm} \times 36.7\text{mm})$	Applications	Medical
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Efficiency	Level V
Size / Dimension 4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.28" L x 2.44" W x 1.45" H (108.7mm x 62.0mm x 36.7mm)
		Report errors?

#### EMMA150200-P6P-IC Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### EMMA150200-P6P-IC Payment Methods



















### EMMA150200-P6P-IC Shipping Methods













If you have any question about EMMA150200-P6P-IC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com