



## **EN3P12F26X Information**

Heisener.com

**Part Number** EN3P12F26X **Manufacturer** Switchcraft Inc.

Category Connectors, Interconnects Circular Connectors

**Description** CONN RCPT 12POS FEMALE PANEL #26

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **EN3P12F26X Specifications**

Manufacturer Part Number       EN3P12F26X         Manufacturer       Switchcraft Inc.         Category       Connectors, Interconnects         Package       -         Series       EN3?         Connector Type       Receptacle, Female Sockets         Number of Positions       12         Shell Size - Insert       -         Shell Size, MIL       -         Mounting Type       Panel Mount, Bulkhead - Front Side Nut         Termination       Solder Cup         Fastening Type       Bayonet Lock         Orientation       Keyed         Ingress Protection       IP66/68 - Dust Tight, Water Resistant, Waterproof         Shell Material, Finish       Thermoplastic Polymer, Glass Fiber         Contact Finish       Gold         Features       -         Voltage - Rated       250VAC/DC         Current Rating       3A         Report errors?	•	
Category Circular Connectors Circular Connectors  Package - Series EN3? Connector Type Receptacle, Female Sockets Number of Positions 12 Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Shell Material, Finish Thermoplastic Polymer, Glass Fiber Contact Finish Gold Features - Voltage - Rated Current Rating 3A	Manufacturer Part Number	EN3P12F26X
Package-SeriesEN3?Connector TypeReceptacle, Female SocketsNumber of Positions12Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplastic Polymer, Glass FiberContact FinishGoldFeatures-Voltage - Rated250VAC/DCCurrent Rating3A	Manufacturer	Switchcraft Inc.
Package - Series EN3? Connector Type Receptacle, Female Sockets Number of Positions 12 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A	Category	Connectors, Interconnects
SeriesEN3?Connector TypeReceptacle, Female SocketsNumber of Positions12Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplastic Polymer, Glass FiberContact FinishGoldFeatures-Voltage - Rated250VAC/DCCurrent Rating3A		Circular Connectors
Connector Type Receptacle, Female Sockets  Number of Positions 12  Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Solder Cup  Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Polymer, Glass Fiber  Contact Finish Gold  Features - Voltage - Rated 250VAC/DC  Current Rating 3A	Package	-
Number of Positions  Shell Size - Insert  - Shell Size, MIL  Mounting Type  Panel Mount, Bulkhead - Front Side Nut  Termination  Solder Cup  Fastening Type  Bayonet Lock  Orientation  Keyed  Ingress Protection  IP66/68 - Dust Tight, Water Resistant, Waterproof  Shell Material, Finish  Thermoplastic Polymer, Glass Fiber  Contact Finish  Gold  Features  - Voltage - Rated  250VAC/DC  Current Rating  3A	Series	EN3?
Shell Size - Insert  Shell Size, MIL  Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Solder Cup Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Polymer, Glass Fiber Contact Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Solder Cup  Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Polymer, Glass Fiber Contact Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A	Number of Positions	12
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplastic Polymer, Glass FiberContact FinishGoldFeatures-Voltage - Rated250VAC/DCCurrent Rating3A	Shell Size - Insert	-
Termination Solder Cup Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Polymer, Glass Fiber Contact Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Polymer, Glass Fiber Contact Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Polymer, Glass Fiber Contact Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A	Termination	Solder Cup
Ingress Protection  IP66/68 - Dust Tight, Water Resistant, Waterproof  Thermoplastic Polymer, Glass Fiber  Contact Finish  Gold  Features  -  Voltage - Rated  250VAC/DC  Current Rating  3A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  - Voltage - Rated  Current Rating  Thermoplastic Polymer, Glass Fiber  Gold  - 3A	Orientation	Keyed
Contact Finish Gold  Features - Voltage - Rated 250VAC/DC  Current Rating 3A	Ingress Protection	IP66/68 - Dust Tight, Water Resistant, Waterproof
Features - Voltage - Rated 250VAC/DC Current Rating 3A	Shell Material, Finish	Thermoplastic Polymer, Glass Fiber
Voltage - Rated 250VAC/DC Current Rating 3A	Contact Finish	Gold
Current Rating 3A	Features	-
-	Voltage - Rated	250VAC/DC
Report errors?	Current Rating	3A
		Report errors?

#### **EN3P12F26X Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **EN3P12F26X Payment Methods**





















### **EN3P12F26X Shipping Methods**













If you have any question about EN3P12F26X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com