



# **EN3P17M26SX Information**

Heisener.com

**Part Number** EN3P17M26SX **Manufacturer** Switchcraft Inc.

Category Connectors, Interconnects Circular Connectors

**Description** CONN RCPT 17POS MALE PANEL #26

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **EN3P17M26SX Specifications**

Manufacturer Part NumberEN3P17M26SXManufacturerSwitchcraft Inc.CategoryConnectors, InterconnectsPackage-SeriesEN3?Connector TypeReceptacle, Male PinsNumber of Positions17Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplastic Polymer, Glass FiberContact FinishGoldFeatures-Voltage - Rated250VAC/DCCurrent Rating3AReport errors?	•	
CategoryConnectors, InterconnectsPackage-SeriesEN3?Connector TypeReceptacle, Male PinsNumber of Positions17Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplastic Polymer, Glass FiberContact FinishGoldFeatures-Voltage - Rated250VAC/DCCurrent Rating3A	Manufacturer Part Number	EN3P17M26SX
Package-SeriesEN3?Connector TypeReceptacle, Male PinsNumber of Positions17Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplastic Polymer, Glass FiberContact FinishGoldFeatures-Voltage - Rated250VAC/DCCurrent Rating3A	Manufacturer	Switchcraft Inc.
Package-SeriesEN3?Connector TypeReceptacle, Male PinsNumber of Positions17Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplastic Polymer, Glass FiberContact FinishGoldFeatures-Voltage - Rated250VAC/DCCurrent Rating3A	Category	Connectors, Interconnects
SeriesEN3?Connector TypeReceptacle, Male PinsNumber of Positions17Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplastic Polymer, Glass FiberContact FinishGoldFeatures-Voltage - Rated250VAC/DCCurrent Rating3A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions17Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplastic Polymer, Glass FiberContact FinishGoldFeatures-Voltage - Rated250VAC/DCCurrent Rating3A	Package	-
Number of Positions17Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplastic Polymer, Glass FiberContact FinishGoldFeatures-Voltage - Rated250VAC/DCCurrent Rating3A	Series	EN3?
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Polymer, Glass Fiber Contact Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Solder Cup  Fastening Type Bayonet Lock Orientation Keyed  Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Polymer, Glass Fiber  Contact Finish Gold  Features -  Voltage - Rated 250VAC/DC  Current Rating 3A	Number of Positions	17
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplastic Polymer, Glass FiberContact FinishGoldFeatures-Voltage - Rated250VAC/DCCurrent Rating3A	Shell Size - Insert	-
Termination Solder Cup Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Polymer, Glass Fiber Contact Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Polymer, Glass Fiber Contact Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Polymer, Glass Fiber Contact Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A	Termination	Solder Cup
Ingress Protection  IP66/68 - Dust Tight, Water Resistant, Waterproof  Shell Material, Finish  Contact Finish  Gold  Features  -  Voltage - Rated  Current Rating  IP66/68 - Dust Tight, Water Resistant, Waterproof  Thermoplastic Polymer, Glass Fiber  Gold  -  250VAC/DC  3A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating 3A Thermoplastic Polymer, Glass Fiber Gold Current Rating	Orientation	Keyed
Contact Finish Gold  Features - Voltage - Rated 250VAC/DC  Current Rating 3A	Ingress Protection	IP66/68 - Dust Tight, Water Resistant, Waterproof
Features - Voltage - Rated 250VAC/DC Current Rating 3A	Shell Material, Finish	Thermoplastic Polymer, Glass Fiber
Voltage - Rated 250VAC/DC Current Rating 3A	Contact Finish	Gold
Current Rating 3A	Features	-
-	Voltage - Rated	250VAC/DC
Report errors?	Current Rating	3A
		Report errors?

#### **EN3P17M26SX Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **EN3P17M26SX Payment Methods**



















### **EN3P17M26SX Shipping Methods**













If you have any question about EN3P17M26SX, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com