



EN3P9M26X Information

Heisener.com

Part Number EN3P9M26X
Manufacturer Switchcraft Inc.

Category Connectors, Interconnects Circular Connectors

Description CONN RCPT 9POS MALE PANEL #26

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EN3P9M26X Specifications

Manufacturer Part Number EN3P9M26X Manufacturer Switchcraft Inc. Category Connectors, Interconnects Package - Series EN3? Connector Type Receptacle, Male Pins Number of Positions 9 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Polymer, Glass Fiber Contact Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A		
CategoryConnectors, InterconnectsPackage-SeriesEN3?Connector TypeReceptacle, Male PinsNumber of Positions9Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplastic Polymer, Glass FiberContact FinishGoldFeatures-Voltage - Rated250VAC/DCCurrent Rating3A	Manufacturer Part Number	EN3P9M26X
Package-SeriesEN3?Connector TypeReceptacle, Male PinsNumber of Positions9Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplastic Polymer, Glass FiberContact FinishGoldFeatures-Voltage - Rated250VAC/DCCurrent Rating3A	Manufacturer	Switchcraft Inc.
Package - Series EN3? Connector Type Receptacle, Male Pins Number of Positions 9 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Gold Features - Contact Finish Gold Current Rating 3A	Category	Connectors, Interconnects
SeriesEN3?Connector TypeReceptacle, Male PinsNumber of Positions9Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplastic Polymer, Glass FiberContact FinishGoldFeatures-Voltage - Rated250VAC/DCCurrent Rating3A		Circular Connectors
Connector Type Receptacle, Male Pins Number of Positions 9 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Polymer, Glass Fiber Contact Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A	Package	-
Number of Positions Shell Size - Insert - Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Polymer, Glass Fiber Contact Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A	Series	EN3?
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Polymer, Glass Fiber Contact Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Polymer, Glass Fiber Contact Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A	Number of Positions	9
Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Polymer, Glass Fiber Contact Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A	Shell Size - Insert	-
Termination Solder Cup Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Polymer, Glass Fiber Contact Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Polymer, Glass Fiber Contact Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Polymer, Glass Fiber Contact Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A	Termination	Solder Cup
Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Thermoplastic Polymer, Glass Fiber Contact Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Thermoplastic Polymer, Glass Fiber Gold - 3A	Orientation	Keyed
Contact Finish Gold Features - Voltage - Rated 250VAC/DC Current Rating 3A	Ingress Protection	IP66/68 - Dust Tight, Water Resistant, Waterproof
Features - Voltage - Rated 250VAC/DC Current Rating 3A	Shell Material, Finish	Thermoplastic Polymer, Glass Fiber
Voltage - Rated 250VAC/DC Current Rating 3A	Contact Finish	Gold
Current Rating 3A	Features	-
-	Voltage - Rated	250VAC/DC
D	Current Rating	3A
Report errors?		Report errors?

EN3P9M26X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EN3P9M26X Payment Methods





















EN3P9M26X Shipping Methods













If you have any question about EN3P9M26X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com