



EPG.0B.309.HLN Information

Heisener.com

Part Number EPG.0B.309.HLN

Manufacturer LEMO

Category Connectors, Interconnects

Circular Connectors

Description CONN R/A PCB RCPT 9SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EPG.0B.309.HLN Specifications

Manufacturer Part Number EPG.0B.309.HLN Manufacturer LEMO Category Connectors, Interconnects Package - Series 0B Connector Type Receptacle, Female Sockets Number of Positions 9 Shell Size - Insert 309 Shell Size, MIL - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 2A		
CategoryConnectors, InterconnectsPackage-Series0BConnector TypeReceptacle, Female SocketsNumber of Positions9Shell Size - Insert309Shell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating2A	Manufacturer Part Number	EPG.0B.309.HLN
Package-Series0BConnector TypeReceptacle, Female SocketsNumber of Positions9Shell Size - Insert309Shell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating2A	Manufacturer	LEMO
Package-Series0BConnector TypeReceptacle, Female SocketsNumber of Positions9Shell Size - Insert309Shell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating2A	Category	Connectors, Interconnects
Series 0B Connector Type Receptacle, Female Sockets Number of Positions 9 Shell Size - Insert 309 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions9Shell Size - Insert309Shell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating2A	Package	-
Number of Positions9Shell Size - Insert309Shell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating2A	Series	0B
Shell Size - Insert309Shell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating2A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated Current Rating 2A	Number of Positions	9
Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationGIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating2A	Shell Size - Insert	309
Termination Solder Fastening Type Push-Pull Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated Current Rating 2A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 2A	Mounting Type	Through Hole, Right Angle
Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 2A	Termination	Solder
Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 2A	Fastening Type	Push-Pull
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Polyphenylene Sulfide (PPS) Gold Shielded	Orientation	G
Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 2A	Ingress Protection	IP50 - Dust Protected
Features Shielded Voltage - Rated - Current Rating 2A	Shell Material, Finish	Polyphenylene Sulfide (PPS)
Voltage - Rated Current Rating 2A	Contact Finish	Gold
Current Rating 2A	Features	Shielded
	Voltage - Rated	-
Report errors?	Current Rating	2A
		Report errors?

EPG.0B.309.HLN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EPG.0B.309.HLN Payment Methods



















EPG.0B.309.HLN Shipping Methods













If you have any question about EPG.0B.309.HLN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com