



EPG.1B.308.HLN Information



For Reference Only

Part Number EPG.1B.308.HLN

Manufacturer LEMO

Category Connectors, Interconnects

Circular Connectors

Description CONN R/A PCB RCPT 8SKT

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EPG.1B.308.HLN Specifications

| Manufacturer Part NumberEPG.1B.308.HLNManufacturerLEMOCategoryConnectors, Interconnects Circular ConnectorsPackage-Series1BConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert308Shell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating2A | | |
|---|--------------------------|-----------------------------|
| Category Connectors, Interconnects Circular Connectors Package - Series 1B Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert 308 Shell Size, MIL - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated - | Manufacturer Part Number | EPG.1B.308.HLN |
| Package-Series1BConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert308Shell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesShieldedVoltage - Rated- | Manufacturer | LEMO |
| Package - Series 1B Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert 308 Shell Size, MIL - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated | Category | Connectors, Interconnects |
| Series 1B Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert 308 Shell Size, MIL - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated | | Circular Connectors |
| Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert 308 Shell Size, MIL - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated - | Package | - |
| Number of Positions Shell Size - Insert 308 Shell Size, MIL Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated - | Series | 1B |
| Shell Size - Insert Shell Size, MIL Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated - | Connector Type | Receptacle, Female Sockets |
| Shell Size, MIL Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated - | Number of Positions | 8 |
| Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesShieldedVoltage - Rated- | Shell Size - Insert | 308 |
| Termination Solder Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated - | Shell Size, MIL | - |
| Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated - | Mounting Type | Through Hole, Right Angle |
| Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated - | Termination | Solder |
| Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated - | Fastening Type | Push-Pull, Detent Lock |
| Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Polyphenylene Sulfide (PPS) Gold | Orientation | G |
| Contact Finish Gold Features Shielded Voltage - Rated - | Ingress Protection | IP50 - Dust Protected |
| Features Shielded Voltage - Rated - | Shell Material, Finish | Polyphenylene Sulfide (PPS) |
| Voltage - Rated - | Contact Finish | Gold |
| | Features | Shielded |
| Current Rating 2A | Voltage - Rated | - |
| | Current Rating | 2A |
| Report errors? | | Report errors? |

EPG.1B.308.HLN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EPG.1B.308.HLN Payment Methods



















EPG.1B.308.HLN Shipping Methods













If you have any question about EPG.1B.308.HLN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com