



EPS120050-P5RP Information



For Reference Only

Part Number EPS120050-P5RP

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 12V 6W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EPS120050-P5RP Specifications

Manufacturer Part Number EPS120050-P5RP Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series EPS Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 132 VAC Voltage - Output 12V Current - Output (Max) 500mA Power (Watts) 6W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series EPS Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 132 VAC Voltage - Output 12V Current - Output (Max) 500mA Power (Watts) 6W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)	Manufacturer Part Number	EPS120050-P5RP
Package - Series EPS Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 132 VAC Voltage - Output 12V Current - Output (Max) 500mA Power (Watts) 6W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)	Manufacturer	CUI Inc.
Package - Series EPS Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 132 VAC Voltage - Output 12V Current - Output (Max) 500mA Power (Watts) 6W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesEPSRegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input $100 \sim 132 \text{ VAC}$ Voltage - Output $12V$ Current - Output (Max) 500mA Power (Watts) $6W$ No Load Power Consumption 300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mmSize / Dimension $2.45^{\circ}\text{ L} \times 1.06^{\circ}\text{ W} \times 1.65^{\circ}\text{ H} (62.3mm \times 26.8mm \times 42.0mm)$		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 132 VAC Voltage - Output 12V Current - Output (Max) 500mA Power (Watts) No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension North America North America North America North America North America 100 ~ 132 VAC Noll Max 100 ~ 132 VAC Wall Mount 100 ~ 132 VAC Voltage - Input 100 ~ 132 VAC Wall Mount 100 ~ 132 VAC Voltage - Input 100 ~ 132 VAC Voltage - In	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input $100 \sim 132 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) 500mA Power (Watts) 6W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 2.45° L x 1.06° W x 1.65° H (62.3mm x 26.8mm x 42.0mm)	Series	EPS
Input Type Fixed Blade Voltage - Input 100 ~ 132 VAC Voltage - Output 12V Current - Output (Max) Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension Fixed Blade 100 ~ 132 VAC 6W Fixed Blade 100 ~ 132 VAC 6W Fixed Blade 100 ~ 132 VAC 6W Fixed Blade 100 ~ 132 VAC 6W Fixed Blade 100 ~ 132 VAC 6W Fixed Blade 100 ~ 132 VAC 6W Fixed Blade 100 ~ 132 VAC 6W Fixed Blade 100 ~ 132 VAC 6W Fixed Blade 100 ~ 132 VAC 6W Fixed Blade 100 ~ 132 VAC 6W Fixed Blade 100 ~ 132 VAC 6W Fixed Blade 100 ~ 132 VAC 6W Fixed Blade 100 ~ 132 VAC 6W Fixed Blade 6W F	Region Utilized	North America
Voltage - Input $100 \sim 132 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) 500mA Power (Watts) 6W No Load Power Consumption 300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.1mm I.D. $x 5.5\text{mm}$ O.D. $x 12.0\text{mm}$ Size / Dimension 2.45° L $x 1.06^{\circ}$ W $x 1.65^{\circ}$ H (62.3mm x 26.8mm x 42.0mm)	Form	Wall Mount
Voltage - Output (Max) 500mA Power (Watts) 6W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)	Input Type	Fixed Blade
Current - Output (Max) Fower (Watts) No Load Power Consumption Output Connector Size / Dimension 500mA 6W 800 No Load Power Consumption 300mW (Max) Positive Center ITE (Commercial) Level V Operating Temperature O°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm 2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)	Voltage - Input	100 ~ 132 VAC
Power (Watts) 6W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)	Voltage - Output	12V
No Load Power Consumption 300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.1mm I.D. $x 5.5 \text{mm}$ O.D. $x 12.0 \text{mm}$ Size / Dimension 2.45° L $x 1.06^{\circ}$ W $x 1.65^{\circ}$ H (62.3mm $x 26.8 \text{mm}$ $x 42.0 \text{mm}$)	Current - Output (Max)	500mA
Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)	Power (Watts)	6W
Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, $2.1 \text{mm I.D. x } 5.5 \text{mm O.D. x } 12.0 \text{mm}$ Size / Dimension $2.45^{\circ}\text{L x } 1.06^{\circ}\text{W x } 1.65^{\circ}\text{H } (62.3 \text{mm x } 26.8 \text{mm x } 42.0 \text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension $2.45^{\circ}\text{L} \times 1.06^{\circ}\text{W} \times 1.65^{\circ}\text{H} (62.3\text{mm} \times 26.8\text{mm} \times 42.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)	Efficiency	Level V
Size / Dimension 2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm
Report errors?	Size / Dimension	2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)
		Report errors?

EPS120050-P5RP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EPS120050-P5RP Payment Methods





















EPS120050-P5RP Shipping Methods













If you have any question about EPS120050-P5RP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com