



### **EPS150040-P5RP Information**

Heisener.com

Part Number EPS150040-P5RP

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC WALL MOUNT ADAPTER 15V 6W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **EPS150040-P5RP Specifications**

Manufacturer Part Number         EPS150040-P5RP           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         EPS           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         100 ~ 132 VAC           Voltage - Output         15V           Current - Output (Max)         400mA           Power (Watts)         6W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         EPS           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         100 ~ 132 VAC           Voltage - Output         15V           Current - Output (Max)         400mA           Power (Watts)         6W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)	Manufacturer Part Number	EPS150040-P5RP
Package         -           Series         EPS           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         100 ~ 132 VAC           Voltage - Output         15V           Current - Output (Max)         400mA           Power (Watts)         6W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)	Manufacturer	CUI Inc.
Package         -           Series         EPS           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         100 ~ 132 VAC           Voltage - Output         15V           Current - Output (Max)         400mA           Power (Watts)         6W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesEPSRegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input $100 \sim 132 \text{ VAC}$ Voltage - Output $15\text{V}$ Current - Output (Max) $400\text{mA}$ Power (Watts) $6\text{W}$ No Load Power Consumption $300\text{mW}$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mmSize / Dimension $2.45^{\circ}\text{ L} \times 1.06^{\circ}\text{ W} \times 1.65^{\circ}\text{ H} (62.3mm \times 26.8mm \times 42.0mm)$		AC DC Desktop, Wall Adapters
Region Utilized  North America  Form  Wall Mount  Input Type Fixed Blade  Voltage - Input 100 ~ 132 VAC  Voltage - Output 15V  Current - Output (Max) 400mA  Power (Watts) 6W  No Load Power Consumption 300mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension  North America North America  North America  North America  North America  100 ~ 132 VAC  Noll Max  400mA  400mA  Fower (Watts) 6W  Operating Temperature 100 °C ~ 40°C  Output Connector 100 C ~ 40°C	Package	-
Form Wall Mount Input Type Fixed Blade  Voltage - Input 100 ~ 132 VAC  Voltage - Output 15V  Current - Output (Max) 400mA  Power (Watts) 6W  No Load Power Consumption 300mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension 2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)	Series	EPS
Input Type Fixed Blade  Voltage - Input  100 ~ 132 VAC  Voltage - Output  15V  Current - Output (Max)  Power (Watts)  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension  Fixed Blade  For 100 ~ 132 VAC  Adomana  400mA  Fow Fixed Blade  Fixed Blade  Fixed Blade  For 100 ~ 132 VAC  Adomana  400mA  Fow Fixed Blade  For 100 ~ 132 VAC  For 100 ~ 132 V	Region Utilized	North America
Voltage - Input $100 \sim 132 \text{ VAC}$ Voltage - Output $15\text{V}$ Current - Output (Max) $400\text{mA}$ Power (Watts) $6\text{W}$ No Load Power Consumption $300\text{mW}$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, $2.1\text{mm}$ I.D. $x 5.5\text{mm}$ O.D. $x 12.0\text{mm}$ Size / Dimension $2.45^{\circ}$ L $x 1.06^{\circ}$ W $x 1.65^{\circ}$ H ( $62.3\text{mm}$ x $26.8\text{mm}$ x $42.0\text{mm}$ )	Form	Wall Mount
Voltage - Output  Current - Output (Max)  400mA  Power (Watts)  6W  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension  15V  400mA  100mA  100mW (Max)  Positive Center  400mA  100mW (Max)  Positive Center  400mM  100mm (Max)  1	Input Type	Fixed Blade
Current - Output (Max)  400mA  Power (Watts)  6W  No Load Power Consumption  300mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension  2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)	Voltage - Input	100 ~ 132 VAC
Power (Watts) 6W  No Load Power Consumption 300mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension 2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)	Voltage - Output	15V
No Load Power Consumption $300 \text{mW}$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, $2.1 \text{mm}$ I.D. $x 5.5 \text{mm}$ O.D. $x 12.0 \text{mm}$ Size / Dimension $2.45^{\circ}$ L $x 1.06^{\circ}$ W $x 1.65^{\circ}$ H ( $62.3 \text{mm}$ $x 26.8 \text{mm}$ $x 42.0 \text{mm}$ )	Current - Output (Max)	400mA
Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, $2.1\text{mm I.D. x } 5.5\text{mm O.D. x } 12.0\text{mm}$ Size / Dimension $2.45^{\circ}\text{L x } 1.06^{\circ}\text{W x } 1.65^{\circ}\text{H } (62.3\text{mm x } 26.8\text{mm x } 42.0\text{mm})$	Power (Watts)	6W
Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension 2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)	No Load Power Consumption	300mW (Max)
Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, $2.1 \text{mm I.D. x } 5.5 \text{mm O.D. x } 12.0 \text{mm}$ Size / Dimension $2.45^{\circ}\text{L x } 1.06^{\circ}\text{W x } 1.65^{\circ}\text{H } (62.3 \text{mm x } 26.8 \text{mm x } 42.0 \text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension $2.45^{\circ}\text{L} \times 1.06^{\circ}\text{W} \times 1.65^{\circ}\text{H} (62.3\text{mm} \times 26.8\text{mm} \times 42.0\text{mm})$	Applications	ITE (Commercial)
Output Connector         Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)	Efficiency	Level V
Size / Dimension 2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)	Operating Temperature	$0^{\circ}\text{C} \sim 40^{\circ}\text{C}$
	Output Connector	Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm
Report errors?	Size / Dimension	2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)
		Report errors?

#### **EPS150040-P5RP Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **EPS150040-P5RP Payment Methods**



















### **EPS150040-P5RP Shipping Methods**













If you have any question about EPS150040-P5RP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com