



EPS240025-P5RP Information

Heisener.com

Part Number EPS240025-P5RP

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 24V 6W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EPS240025-P5RP Specifications

Manufacturer Part NumberEPS240025-P5RPManufacturerCUI Inc.CategoryPower Supplies - External/Internal (Off-Board)Package-SeriesEPSRegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input100 ~ 132 VACVoltage - Output24VCurrent - Output (Max)250mAPower (Watts)6WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesEPSRegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input100 ~ 132 VACVoltage - Output24VCurrent - Output (Max)250mAPower (Watts)6WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°C	Manufacturer Part Number	EPS240025-P5RP
Package - Series EPS Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 132 VAC Voltage - Output 24V Current - Output (Max) 250mA Power (Watts) 6W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Over 40°C	Manufacturer	CUI Inc.
Package-SeriesEPSRegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input100 ~ 132 VACVoltage - Output24VCurrent - Output (Max)250mAPower (Watts)6WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°C	Category	Power Supplies - External/Internal (Off-Board)
SeriesEPSRegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input $100 \sim 132 \text{ VAC}$ Voltage - Output 24V Current - Output (Max) 250mA Power (Watts) 6W No Load Power Consumption 300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 132 VAC Voltage - Output 24V Current - Output (Max) Power (Watts) No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature North America North America North America North America Wall Mount 100 ~ 132 VAC 4V Current - Output (Max) 250mA Power (Watts) 6W Som Watts 100 ~ 132 VAC 24V 100 ~ 132 VAC 100 ~ 132 VAC 24V 100 ~ 132 VAC 100 ~ 132 VAC 100 ~ 132 VAC 100 ~ 132 VAC 24V 100 ~ 132 VAC 100 ~ 132 VAC 24V 100 ~ 132 VAC 100 ~ 132 VAC 24V 250mA Power (Watts) 100 ~ 132 VAC 100 ~ 132 VAC 100 ~ 132 VAC 100 ~ 132 VAC 100 ~ 1	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 132 VAC Voltage - Output 24V Current - Output (Max) 250mA Power (Watts) 6W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C	Series	EPS
Input Type Fixed Blade Voltage - Input 100 ~ 132 VAC Voltage - Output 24V Current - Output (Max) 250mA Power (Watts) 6W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature Fixed Blade Fixed Blade Ito Commercial 100 ~ 132 VAC 4V Current - Output 6W Level V Operating Temperature Fixed Blade Ito Commercial 100 ~ 132 VAC 100 ~ 132 VAC 100 ~ 132 VAC 100 ~ 132 VAC 100 ~ 132 VAC 100 ~ 13	Region Utilized	North America
Voltage - Input 100 ~ 132 VAC Voltage - Output 24V Current - Output (Max) 250mA Power (Watts) No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature	Form	Wall Mount
Voltage - Output Current - Output (Max) 250mA Power (Watts) 6W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C	Input Type	Fixed Blade
Current - Output (Max) Power (Watts) 6W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 250mA 6W Current - Output (Max) 6W Level V Operating Temperature	Voltage - Input	100 ~ 132 VAC
Power (Watts) 6W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C	Voltage - Output	24V
No Load Power Consumption 300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$	Current - Output (Max)	250mA
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature 0° C ~ 40° C	Power (Watts)	6W
Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$	Applications	ITE (Commercial)
	Efficiency	Level V
Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm
Size / Dimension 2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)	Size / Dimension	2.45" L x 1.06" W x 1.65" H (62.3mm x 26.8mm x 42.0mm)
Report errors?		Report errors?

EPS240025-P5RP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EPS240025-P5RP Payment Methods



















EPS240025-P5RP Shipping Methods













If you have any question about EPS240025-P5RP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com