

Heisener.com

# EPSA090130U-P6RP-EJ

### **EPSA090130U-P6RP-EJ Information**

Part Number EPSA090130U-P6RP-EJ

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC WALL MOUNT ADAPTER 9V 12W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **EPSA090130U-P6RP-EJ Specifications**

Manufacturer Part Number         EPSA090130U-P6RP-EJ           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           Rekage         -           Series         EPSA           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         9V           Current - Output (Max)         1.3A           Power (Watts)         12W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.95" L x 1.38" W x 1.85" H (75.0mm x 35.0mm x 47.0mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         EPSA           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         9V           Current - Output (Max)         1.3A           Power (Watts)         12W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.95" L x 1.38" W x 1.85" H (75.0mm x 35.0mm x 47.0mm)	Manufacturer Part Number	EPSA090130U-P6RP-EJ
Package         -           Series         EPSA           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         9V           Current - Output (Max)         1.3A           Power (Watts)         12W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.95" L x 1.38" W x 1.85" H (75.0mm x 35.0mm x 47.0mm)	Manufacturer	CUI Inc.
Package         -           Series         EPSA           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         9V           Current - Output (Max)         1.3A           Power (Watts)         12W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.95" L x 1.38" W x 1.85" H (75.0mm x 35.0mm x 47.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesEPSARegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output9VCurrent - Output (Max)1.3APower (Watts)12WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.95" L x 1.38" W x 1.85" H (75.0mm x 35.0mm x 47.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 1.3A Power (Watts) 12W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.38" W x 1.85" H (75.0mm x 35.0mm x 47.0mm)	Package	-
Form Wall Mount Input Type Fixed Blade  Voltage - Input 90 ~ 264 VAC  Voltage - Output 9V  Current - Output (Max) 1.3A  Power (Watts) 12W  No Load Power Consumption 300mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.95" L x 1.38" W x 1.85" H (75.0mm x 35.0mm x 47.0mm)	Series	EPSA
Input Type Fixed Blade  Voltage - Input 90 ~ 264 VAC  Voltage - Output 9V  Current - Output (Max) 1.3A  Power (Watts) 12W  No Load Power Consumption 300mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.95" L x 1.38" W x 1.85" H (75.0mm x 35.0mm x 47.0mm)	Region Utilized	North America
Voltage - Input  90 ~ 264 VAC  Voltage - Output  9V  Current - Output (Max)  1.3A  Power (Watts)  No Load Power Consumption  300mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  2.95" L x 1.38" W x 1.85" H (75.0mm x 35.0mm x 47.0mm)	Form	Wall Mount
Voltage - Output 9V  Current - Output (Max) 1.3A  Power (Watts) 12W  No Load Power Consumption 300mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.95" L x 1.38" W x 1.85" H (75.0mm x 35.0mm x 47.0mm)	Input Type	Fixed Blade
Current - Output (Max)  1.3A  Power (Watts)  12W  No Load Power Consumption  300mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  2.95" L x 1.38" W x 1.85" H (75.0mm x 35.0mm x 47.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts)  12W  No Load Power Consumption  300mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  2.95" L x 1.38" W x 1.85" H (75.0mm x 35.0mm x 47.0mm)	Voltage - Output	9V
No Load Power Consumption 300mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.95" L x 1.38" W x 1.85" H (75.0mm x 35.0mm x 47.0mm)	Current - Output (Max)	1.3A
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension $2.95$ " L x $1.38$ " W x $1.85$ " H $(75.0\text{mm x } 35.0\text{mm x } 47.0\text{mm})$	Power (Watts)	12W
Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.95" L x 1.38" W x 1.85" H (75.0mm x 35.0mm x 47.0mm)	No Load Power Consumption	300mW (Max)
Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.95" L x 1.38" W x 1.85" H (75.0mm x 35.0mm x 47.0mm)	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $2.95^{\circ}\text{L} \times 1.38^{\circ}\text{W} \times 1.85^{\circ}\text{H} (75.0\text{mm} \times 35.0\text{mm} \times 47.0\text{mm})$	Applications	ITE (Commercial)
Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.95" L x 1.38" W x 1.85" H (75.0mm x 35.0mm x 47.0mm)	Efficiency	Level V
Size / Dimension 2.95" L x 1.38" W x 1.85" H (75.0mm x 35.0mm x 47.0mm)	Operating Temperature	$0^{\circ}\text{C} \sim 40^{\circ}\text{C}$
	Output Connector	Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	2.95" L x 1.38" W x 1.85" H (75.0mm x 35.0mm x 47.0mm)
		Report errors?

#### EPSA090130U-P6RP-EJ Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### EPSA090130U-P6RP-EJ Payment Methods



















## EPSA090130U-P6RP-EJ Shipping Methods













If you have any question about EPSA090130U-P6RP-EJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com