

Heisener.com

# EPSA240100U-P6RP-SZ

### EPSA240100U-P6RP-SZ Information

Part Number EPSA240100U-P6RP-SZ

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC WALL MOUNT ADAPTER 24V 24W

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **EPSA240100U-P6RP-SZ Specifications**

Manufacturer Part Number         EPSA240100U-P6RP-SZ           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         EPSA           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         1A           Power (Watts)         24W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         3.15" L x 1.38" W x 2.11" H (80.0mm x 35.0mm x 53.6mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         EPSA           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         1A           Power (Watts)         24W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         3.15" L x 1.38" W x 2.11" H (80.0mm x 35.0mm x 53.6mm)	Manufacturer Part Number	EPSA240100U-P6RP-SZ
Package         -           Series         EPSA           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         1A           Power (Watts)         24W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         3.15" L x 1.38" W x 2.11" H (80.0mm x 35.0mm x 53.6mm)	Manufacturer	CUI Inc.
Package         -           Series         EPSA           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         1A           Power (Watts)         24W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         3.15" L x 1.38" W x 2.11" H (80.0mm x 35.0mm x 53.6mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesEPSARegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)1APower (Watts)24WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.15" L x 1.38" W x 2.11" H (80.0mm x 35.0mm x 53.6mm)		AC DC Desktop, Wall Adapters
Region Utilized  Form  Wall Mount  Input Type  Fixed Blade  Voltage - Input  90 ~ 264 VAC  Voltage - Output  Current - Output (Max)  1A  Power (Watts)  No Load Power Consumption  Positive Center  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  North America  North America  North America  Wall Mount  1nput  90 ~ 264 VAC  44V  Current - Output (Max)  1A  Power (Watts)  1A  Power (Watts)  1A  1A  1A  1A  1A  1A  1A  1A  1A  1	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 1A Power (Watts) 24W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.15" L x 1.38" W x 2.11" H (80.0mm x 35.0mm x 53.6mm)	Series	EPSA
Input Type Fixed Blade  Voltage - Input 90 ~ 264 VAC  Voltage - Output 24V  Current - Output (Max) 1A  Power (Watts) 24W  No Load Power Consumption 300mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 3.15" L x 1.38" W x 2.11" H (80.0mm x 35.0mm x 53.6mm)	Region Utilized	North America
Voltage - Input  90 ~ 264 VAC  Voltage - Output  24V  Current - Output (Max)  1A  Power (Watts)  No Load Power Consumption  300mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  3.15" L x 1.38" W x 2.11" H (80.0mm x 35.0mm x 53.6mm)	Form	Wall Mount
Voltage - Output  Current - Output (Max)  1A  Power (Watts)  24W  No Load Power Consumption  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  24V  24V  Current - Output (Max)  1A  Power (Watts)  10  10  10  10  10  10  10  10  10  1	Input Type	Fixed Blade
Current - Output (Max)  Power (Watts)  24W  No Load Power Consumption  300mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  3.15" L x 1.38" W x 2.11" H (80.0mm x 35.0mm x 53.6mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts)  24W  No Load Power Consumption  300mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  3.15" L x 1.38" W x 2.11" H (80.0mm x 35.0mm x 53.6mm)	Voltage - Output	24V
No Load Power Consumption 300mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 3.15" L x 1.38" W x 2.11" H (80.0mm x 35.0mm x 53.6mm)	Current - Output (Max)	1A
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension $3.15$ " L x $1.38$ " W x $2.11$ " H ( $80.0$ mm x $35.0$ mm x $53.6$ mm)	Power (Watts)	24W
Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $3.15^{\circ}\text{L} \times 1.38^{\circ}\text{W} \times 2.11^{\circ}\text{H} (80.0\text{mm} \times 35.0\text{mm} \times 53.6\text{mm})$	No Load Power Consumption	300mW (Max)
Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $3.15^{\circ}\text{L} \times 1.38^{\circ}\text{W} \times 2.11^{\circ}\text{H} (80.0\text{mm} \times 35.0\text{mm} \times 53.6\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension $3.15$ " L x $1.38$ " W x $2.11$ " H ( $80.0$ mm x $35.0$ mm x $53.6$ mm)	Applications	ITE (Commercial)
Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  3.15" L x 1.38" W x 2.11" H (80.0mm x 35.0mm x 53.6mm)	Efficiency	Level V
Size / Dimension 3.15" L x 1.38" W x 2.11" H (80.0mm x 35.0mm x 53.6mm)	Operating Temperature	$0^{\circ}\text{C} \sim 40^{\circ}\text{C}$
	Output Connector	Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	3.15" L x 1.38" W x 2.11" H (80.0mm x 35.0mm x 53.6mm)
		Report errors?

### EPSA240100U-P6RP-SZ Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### EPSA240100U-P6RP-SZ Payment Methods



















### EPSA240100U-P6RP-SZ Shipping Methods













If you have any question about EPSA240100U-P6RP-SZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com