




ERA-14HD300U Information



For Reference Only

Part Number ERA-14HD300U

Manufacturer Panasonic Electronic Components

Category Resistors

Chip Resistor - Surface Mount

Description RES SMD 30 OHM 0.5% 1/4W 1210

Package 1210 (3225 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ERA-14HD300U Specifications

Manufacturer Part Number ERA-14HD300U Manufacturer Panasonic Electronic Components Category Resistors Chip Resistor - Surface Mount Package 1210 (3225 Metric) Series ERA-14 Resistance 30 Ohms Tolerance ±0.5% Power (Watts) 0.25W, 1/4W Composition Thin Film Features - Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	*	
Category Resistors Chip Resistor - Surface Mount Package 1210 (3225 Metric) Series ERA-14 Resistance 30 Ohms Tolerance ±0.5% Power (Watts) 0.25W, 1/4W Composition Thin Film Features - Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Manufacturer Part Number	ERA-14HD300U
Chip Resistor - Surface Mount Package 1210 (3225 Metric) Series ERA-14 Resistance 30 Ohms Tolerance ±0.5% Power (Watts) 0.25W, 1/4W Composition Thin Film Features - Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Manufacturer	Panasonic Electronic Components
Package 1210 (3225 Metric) Series ERA-14 Resistance 30 Ohms Tolerance ±0.5% Power (Watts) 0.25W, 1/4W Composition Thin Film Features - Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Category	Resistors
Series ERA-14 Resistance 30 Ohms Tolerance ±0.5% Power (Watts) 0.25W, 1/4W Composition Thin Film Features - Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -		Chip Resistor - Surface Mount
Resistance 30 Ohms Tolerance ±0.5% Power (Watts) 0.25W, 1/4W Composition Thin Film Features - Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Package	1210 (3225 Metric)
Tolerance ±0.5% Power (Watts) 0.25W, 1/4W Composition Thin Film Features - Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Series	ERA-14
Power (Watts) Composition Thin Film Features - Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Resistance	30 Ohms
Composition Thin Film Features - Temperature Coefficient Departing Temperature -55°C ~ 125°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Tolerance	±0.5%
Features Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Power (Watts)	0.25W, 1/4W
Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Composition	Thin Film
Operating Temperature -55°C ~ 125°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Features	-
Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Temperature Coefficient	±50ppm/°C
Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Operating Temperature	-55°C ~ 125°C
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Package / Case	1210 (3225 Metric)
Height - Seated (Max) Number of Terminations 2 Failure Rate -	Supplier Device Package	1210
Number of Terminations 2 Failure Rate -	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
Failure Rate -	Height - Seated (Max)	0.028" (0.70mm)
	Number of Terminations	2
Report errors?	Failure Rate	-
		Report errors?

ERA-14HD300U Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ERA-14HD300U Payment Methods



















ERA-14HD300U Shipping Methods













If you have any question about ERA-14HD300U, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com