



ERA.3S.314.CLL Information

Heisener.com

Part Number ERA.3S.314.CLL

Manufacturer LEMO

Category Connectors, Interconnects

Circular Connectors

Description CONN PNL MNT RCPT 14SKT SLD CUP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ERA.3S.314.CLL Specifications

Manufacturer Part Number ERA.3S.314.CLL Manufacturer LEMO Category Connectors, Interconnects Package - Series 3S Connector Type Receptacle, Female Sockets and Male Pins Number of Positions 14 Shell Size - Insert 314 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7A		
CategoryConnectors, InterconnectsPackage-Series3SConnector TypeReceptacle, Female Sockets and Male PinsNumber of Positions14Shell Size - Insert314Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7A	Manufacturer Part Number	ERA.3S.314.CLL
Package-Series3SConnector TypeReceptacle, Female Sockets and Male PinsNumber of Positions14Shell Size - Insert314Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7A	Manufacturer	LEMO
Package - Series 3S Connector Type Receptacle, Female Sockets and Male Pins Number of Positions 14 Shell Size - Insert 314 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7A	Category	Connectors, Interconnects
Series 3S Connector Type Receptacle, Female Sockets and Male Pins Number of Positions 14 Shell Size - Insert 314 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Female Sockets and Male PinsNumber of Positions14Shell Size - Insert314Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7A	Package	-
Number of Positions14Shell Size - Insert314Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7A	Series	3S
Shell Size - Insert Shell Size, MIL	Connector Type	Receptacle, Female Sockets and Male Pins
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7A	Number of Positions	14
Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7A	Shell Size - Insert	314
Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7A	Shell Size, MIL	-
Fastening Type Push-Pull, Detent Lock Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7A	Mounting Type	Panel Mount, Bulkhead - Rear Side Nut
Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7A	Termination	Solder Cup
Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7A	Fastening Type	Push-Pull, Detent Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7A	Orientation	Keyed
Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7A	Ingress Protection	IP50 - Dust Protected
Features Shielded Voltage - Rated - Current Rating 7A	Shell Material, Finish	Brass, Chrome Plated
Voltage - Rated - Current Rating 7A	Contact Finish	Gold
Current Rating 7A	Features	Shielded
	Voltage - Rated	-
Report errors?	Current Rating	7A
		Report errors?

ERA.3S.314.CLL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ERA.3S.314.CLL Payment Methods



















ERA.3S.314.CLL Shipping Methods













If you have any question about ERA.3S.314.CLL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com