

ERJ-P08J563V

ERJ-P08J563V Information

| www.teisener.com | ERJ-P08J563V Panasonic Electronic Components Resistors Chip Resistor - Surface Mount RES SMD 56K OHM 5% 2/3W 1206 1206 (3216 Metric) | |
|--------------------|---|-----------------|
| 0.00 | For the pricing/inventory/lead time, please contact us | EI (2) 7 7 5 4 |
| For Reference Only | Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ERJ-P08J563V Specifications

| Manufacturer Part Number ERI-P08J563V Manufacturer Panasonic Electronic Components Category Resistors Chip Resistor - Surface Mount Chip Resistor - Surface Mount Package 1206 (3216 Metric) Series ERJ Resistance 56 kOhms Tolerance ±5% Power (Watts) 0.667W, 2/3W Composition Thick Film Features Automotive AEC-Q200, Pulse Withstanding Perture Coefficient ±200pm/°C Operating Temperature 55°C ~ 155°C Package / Case 1206 (3216 Metric) Supplier Device Package 1206 (3216 Metric) Supplier Device Package 0.028" (0.70mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate - | | | |
|--|--------------------------|---|----------------|
| CategoryResistorsChip Resistor - Surface MountPackage1206 (3216 Metric)SeriesERJResistance56 kOhmsTolerance±5%Power (Watts)0.667W, 2/3WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±200pm/°COperating Temperature55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.28" (0.70mm)Number of Terminations2Failure Rate- | Manufacturer Part Number | ERJ-P08J563V | |
| Chip Resistor - Surface MountPackage1206 (3216 Metric)SeriesERJResistance56 kOhmsTolerance±5%Power (Watts)0.667W, 2/3WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±200ppm/°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)2Automotive AEC - Sinon2 | Manufacturer | Panasonic Electronic Components | |
| Package1206 (3216 Metric)SeriesERJResistance56 kOhmsTolerance±5%Power (Watts)0.667W, 2/3WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingPoperating Temperature±200pm/°COperating Temperature1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)2Number of Terminations2Failure Rate- | Category | Resistors | |
| SeriesERJResistance56 kOhmsTolerance±5%Power (Watts)0.667W, 2/3WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±200pm/°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package0.26° L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.28" (0.70mm)Number of Terminations2Failure Rate- | | Chip Resistor - Surface Mount | |
| Resistance 56 kOhms Tolerance ±5% Power (Watts) 0.667W, 2/3W Composition Thick Film Features Automotive AEC-Q200, Pulse Withstanding Temperature Coefficient ±200pm/°C Operating Temperature -55°C ~ 155°C Package / Case 1206 (3216 Metric) Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate - | Package | 1206 (3216 Metric) | |
| Tolerance±5%Power (Watts)0.667W, 2/3WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±200ppm/°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)0.028" (0.70mm)Number of Terminations2Failure Rate- | Series | ERJ | |
| Power (Watts)0.667W, 2/3WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±200ppm/°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.028" (0.70mm)Number of Terminations2Failure Rate- | Resistance | 56 kOhms | |
| CompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±200pm/°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)0.028° (0.70mm)Number of Terminations2Failure Rate- | Tolerance | ±5% | |
| FeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±200ppm/°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.028" (0.70mm)Number of Terminations2Failure Rate- | Power (Watts) | 0.667W, 2/3W | |
| Temperature Coefficient±200pm/°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.028" (0.70mm)Number of Terminations2Failure Rate- | Composition | Thick Film | |
| Operating Temperature -55°C ~ 155°C Package / Case 1206 (3216 Metric) Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate - | Features | Automotive AEC-Q200, Pulse Withstanding | |
| Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.028" (0.70mm)Number of Terminations2Failure Rate- | Temperature Coefficient | ±200ppm/°C | |
| Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.028" (0.70mm)Number of Terminations2Failure Rate- | Operating Temperature | -55°C ~ 155°C | |
| Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate - | Package / Case | 1206 (3216 Metric) | |
| Height - Seated (Max)0.028" (0.70mm)Number of Terminations2Failure Rate- | Supplier Device Package | 1206 | |
| Number of Terminations2Failure Rate- | Size / Dimension | 0.126" L x 0.063" W (3.20mm x 1.60mm) | |
| Failure Rate - | Height - Seated (Max) | 0.028" (0.70mm) | |
| | Number of Terminations | 2 | |
| Report errors? | Failure Rate | - | |
| | | | Report errors? |

ERJ-P08J563V Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ERJ-P08J563V Payment Methods



ERJ-P08J563V Shipping Methods



If you have any question about ERJ-P08J563V, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com