

ERJ-P14F8872U

ote

ERJ-P14F8872U Information

www.helsener.com	Part Number	ERJ-P14F8872U	
	Manufacturer	Panasonic Electronic Components	
	Category	Resistors Chip Resistor - Surface Mount	
	Description	RES SMD 88.7K OHM 1% 1/2W 1210	15-1235
	Package	1210 (3225 Metric)	1.00
		For the pricing/inventory/lead time, please contact us	E 877
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quo

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ERJ-P14F8872U Specifications

Manufacturer Part NumberERJ-P14F8872UManufacturerPanasonic Electronic ComponentsCategoryResistorsChip Resistor - Surface MountPackage1210 (3225 Metric)SeriesERJResistance88.7 kOhmsTolerance±1%Power (Watts)0.5W, 1/2WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingPertures-55°C ~ 155°CPackage / Case1210 (3225 Metric)Supplier Device Package1210Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)		
CategoryResistorsChip Resistor - Surface MountPackage1210 (3225 Metric)SeriesERJResistance88.7 kOhmsTolerance±1%Power (Watts)0.5W, 1/2WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±100ppm°COperating Temperature-55°C ~ 155°CPackage / Case1210 (3225 Metric)Supplier Device Package1210Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Manufacturer Part Number	ERJ-P14F8872U
Chip Resistor - Surface MountPackage1210 (3225 Metric)SeriesERJResistance88.7 kOhmsTolerance±1%Power (Watts)0.5W, 1/2WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±100pm/°COperating Temperature-55°C ~ 155°CPackage / Case1210 (3225 Metric)Supplier Device Package1210Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Manufacturer	Panasonic Electronic Components
Package1210 (3225 Metric)SeriesERJResistance88.7 kOhmsTolerance±1%Power (Watts)0.5W, 1/2WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±100pm/°COperating Temperature-55°C ~ 155°CPackage / Case1210 (3225 Metric)Supplier Device Package0.126" L x 0.098" W (3.20mm x 2.50mm)	Category	Resistors
SeriesERJResistance88.7 kOhmsTolerance±1%Power (Watts)0.5W, 1/2WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 155°CPackage / Case1210 (3225 Metric)Supplier Device Package1210Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)		Chip Resistor - Surface Mount
Resistance88.7 kOhmsTolerance±1%Power (Watts)0.5W, 1/2WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 155°CPackage / Case1210 (3225 Metric)Supplier Device Package1210Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Package	1210 (3225 Metric)
Tolerance±1%Power (Watts)0.5W, 1/2WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±100pm/°COperating Temperature-55°C ~ 155°CPackage / Case1210 (3225 Metric)Supplier Device Package0.126" L x 0.098" W (3.20mm x 2.50mm)	Series	ERJ
Power (Watts)0.5W, 1/2WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 155°CPackage / Case1210 (3225 Metric)Supplier Device Package1210Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Resistance	88.7 kOhms
CompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±100pm/°COperating Temperature-55°C ~ 155°CPackage / Case1210 (3225 Metric)Supplier Device Package1210Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Tolerance	$\pm 1\%$
FeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 155°CPackage / Case1210 (3225 Metric)Supplier Device Package1210Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Power (Watts)	0.5W, 1/2W
Temperature Coefficient±100ppm/°COperating Temperature-55°C ~ 155°CPackage / Case1210 (3225 Metric)Supplier Device Package1210Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Composition	Thick Film
Operating Temperature-55°C ~ 155°CPackage / Case1210 (3225 Metric)Supplier Device Package1210Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Features	Automotive AEC-Q200, Pulse Withstanding
Package / Case1210 (3225 Metric)Supplier Device Package1210Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Temperature Coefficient	±100ppm/°C
Supplier Device Package1210Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Operating Temperature	-55°C ~ 155°C
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm)	Package / Case	1210 (3225 Metric)
	Supplier Device Package	1210
	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
Height - Seated (Max) $0.028^{\circ}(0.70\text{mm})$	Height - Seated (Max)	0.028" (0.70mm)
Number of Terminations 2	Number of Terminations	2
Failure Rate -	Failure Rate	-
Report error		Report errors?

ERJ-P14F8872U Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ERJ-P14F8872U Payment Methods



ERJ-P14F8872U Shipping Methods



If you have any question about ERJ-P14F8872U, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com