

ERJ-PB3D2672V

uote

ERJ-PB3D2672V Information

www.beisener.com	Category	ERJ-PB3D2672V Panasonic Electronic Components Resistors Chip Resistor - Surface Mount RES SMD 26.7K OHM 0.5% 1/5W 0603	
	Description Package	RES SMD 20.7K OHM 0.5% 1/5 w 00030603 (1608 Metric)For the pricing/inventory/lead time, please contact	E.
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Q

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ERJ-PB3D2672V Specifications

Manufacturer Part NumberERJ-PB3D2672VManufacturerPanasonic Electronic ComponentsCategoryResistorsChip Resistor - Surface MountPackage0603 (1608 Metric)SeriesERJResistance26.7 kOhmsTolerance±0.5%Power (Watts)0.2W, 1/5WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±50pm/°COperating Temperature0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.02" (0.55mm)Height - Seated (Max)0.02" (0.55mm)Number of Terminations2Failure Rate-Failure Rate-Suppler Device Package0.02" (0.55mm)State (Max)0.02" (0.55mm)State (Max)0.2Suppler Device Package-State (Max)0.2Suppler Device Package0.02" (0.55mm)State (Max)0.2State (Max)0.2State (Max)2State (Max)-State (Max)-State (Max)-State (Max)-State (Max)-State (State		
Category Resistors Category Resistors Chip Resistor - Surface Mount Chip Resistor - Surface Mount Package 0603 (1608 Metric) Series ERJ Resistance 26.7 kOhms Tolerance ±0.5% Power (Watts) 0.2W, 1/5W Composition Thick Film Features Automotive AEC-Q200, Pulse Withstanding Temperature Coefficient ±50ppm/°C Operating Temperature 6603 (1608 Metric) Supplier Device Package 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm) Height - Seated (Max) 0.022" (0.55mm) Number of Terminations 2	Manufacturer Part Number	ERJ-PB3D2672V
Chip Resistor - Surface MountPackage0603 (1608 Metric)SeriesERJResistance26.7 kOhmsTolerance±0.5%Power (Watts)0.2W, 1/5WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±50pm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.22" (0.55mm)Number of Terminations2	Manufacturer	Panasonic Electronic Components
Package0603 (1608 Metric)SeriesERJResistance26.7 KOhmsTolerance±0.5%Power (Watts)0.2W, 1/5WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±50pm/°COperating Temperature0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)2	Category	Resistors
SeriesERJResistance26.7 kOhmsTolerance±0.5%Power (Watts)0.2W, 1/5WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±50ppm°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2		Chip Resistor - Surface Mount
Resistance26.7 kOhmsTolerance±0.5%Power (Watts)0.2W, 1/5WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±50pm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.22" (0.55mm)Number of Terminations2	Package	0603 (1608 Metric)
Tolerance±0.5%Power (Watts)0.2W, 1/5WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±50pm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0.603" L x 0.032" W (1.60mm x 0.80mm)Size / Dimension0.022" (0.55mm)Height - Seated (Max)2	Series	ERJ
Power (Watts)0.2W, 1/5WCompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2	Resistance	26.7 kOhms
CompositionThick FilmFeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±50pm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2	Tolerance	$\pm 0.5\%$
FeaturesAutomotive AEC-Q200, Pulse WithstandingTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2	Power (Watts)	0.2W, 1/5W
Temperature Coefficient ±50pm/°C Operating Temperature -55°C ~ 155°C Package / Case 0603 (1608 Metric) Supplier Device Package 0603 Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm) Height - Seated (Max) 0.022" (0.55mm) Number of Terminations 2	Composition	Thick Film
Operating Temperature -55°C ~ 155°C Package / Case 0603 (1608 Metric) Supplier Device Package 0603 Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm) Height - Seated (Max) 0.022" (0.55mm) Number of Terminations 2	Features	Automotive AEC-Q200, Pulse Withstanding
Package / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2	Temperature Coefficient	±50ppm/°C
Supplier Device Package 0603 Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm) Height - Seated (Max) 0.022" (0.55mm) Number of Terminations 2	Operating Temperature	-55°C ~ 155°C
Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm) Height - Seated (Max) 0.022" (0.55mm) Number of Terminations 2	Package / Case	0603 (1608 Metric)
Height - Seated (Max)0.022" (0.55mm)Number of Terminations2	Supplier Device Package	0603
Number of Terminations 2	Size / Dimension	0.063" L x 0.032" W (1.60mm x 0.80mm)
	Height - Seated (Max)	0.022" (0.55mm)
Failure Rate -	Number of Terminations	2
	Failure Rate	-
Report errors?		Report errors?

ERJ-PB3D2672V Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ERJ-PB3D2672V Payment Methods



ERJ-PB3D2672V Shipping Methods



If you have any question about ERJ-PB3D2672V, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com