




ERJ-S14F4303U Information



For Reference Only

Part Number ERJ-S14F4303U

Manufacturer Panasonic Electronic Components

Category Resistors

Chip Resistor - Surface Mount

Description RES SMD 430K OHM 1% 1/2W 1210

Package 1210 (3225 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ERJ-S14F4303U Specifications

Manufacturer Part Number ERJ-S14F4303U Manufacturer Panasonic Electronic Components Category Resistors Chip Resistor - Surface Mount Package 1210 (3225 Metric) Series ERJ Resistance 430 kOhms Tolerance ±1% Power (Watts) 0.5W, 1/2W Composition Thick Film Features Anti-Sulfur, Automotive AEC-Q200 Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 155°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	•	
Category Resistors Chip Resistor - Surface Mount Package 1210 (3225 Metric) Series ERJ Resistance 430 kOhms Tolerance ±1% Power (Watts) 0.5W, 1/2W Composition Thick Film Features Anti-Sulfur, Automotive AEC-Q200 Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 155°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Manufacturer Part Number	ERJ-S14F4303U
Package 1210 (3225 Metric) Series ERJ Resistance 430 kOhms Tolerance ±1% Power (Watts) 0.5W, 1/2W Composition Thick Film Features Anti-Sulfur, Automotive AEC-Q200 Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 155°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Manufacturer	Panasonic Electronic Components
Package 1210 (3225 Metric) Series ERJ Resistance 430 kOhms Tolerance ±1% Power (Watts) 0.5W, 1/2W Composition Thick Film Features Anti-Sulfur, Automotive AEC-Q200 Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 155°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Category	Resistors
SeriesERJResistance430 kOhmsTolerance±1%Power (Watts)0.5W, 1/2WCompositionThick FilmFeaturesAnti-Sulfur, Automotive AEC-Q200Temperature Coefficient±100ppm/°COperating Temperature-55°C ~ 155°CPackage / Case1210 (3225 Metric)Supplier Device Package1210Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.028" (0.70mm)Number of Terminations2Failure Rate-		Chip Resistor - Surface Mount
Resistance 430 kOhms Tolerance ±1% Power (Watts) 0.5W, 1/2W Composition Thick Film Features Anti-Sulfur, Automotive AEC-Q200 Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 155°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Package	1210 (3225 Metric)
Tolerance ±1% Power (Watts) 0.5W, 1/2W Composition Thick Film Features Anti-Sulfur, Automotive AEC-Q200 Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 155°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Series	ERJ
Power (Watts) Composition Thick Film Features Anti-Sulfur, Automotive AEC-Q200 Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 155°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Resistance	430 kOhms
Composition Thick Film Features Anti-Sulfur, Automotive AEC-Q200 Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 155°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Tolerance	±1%
Features Anti-Sulfur, Automotive AEC-Q200 Temperature Coefficient $\pm 100 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 155^{\circ}\text{C}$ Package / Case $1210 (3225 \text{ Metric})$ Supplier Device Package 1210 Size / Dimension $0.126^{\circ}\text{L x } 0.098^{\circ}\text{W } (3.20 \text{mm x } 2.50 \text{mm})$ Height - Seated (Max) $0.028^{\circ} (0.70 \text{mm})$ Number of Terminations 2 Failure Rate	Power (Watts)	0.5W, 1/2W
Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 155°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Composition	Thick Film
Operating Temperature -55°C ~ 155°C Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Features	Anti-Sulfur, Automotive AEC-Q200
Package / Case 1210 (3225 Metric) Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Temperature Coefficient	±100ppm/°C
Supplier Device Package 1210 Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Operating Temperature	-55°C ~ 155°C
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Package / Case	1210 (3225 Metric)
Height - Seated (Max) Number of Terminations 2 Failure Rate -	Supplier Device Package	1210
Number of Terminations 2 Failure Rate -	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
Failure Rate -	Height - Seated (Max)	0.028" (0.70mm)
	Number of Terminations	2
Report errors?	Failure Rate	-
		Report errors?

ERJ-S14F4303U Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ERJ-S14F4303U Payment Methods



















ERJ-S14F4303U Shipping Methods













If you have any question about ERJ-S14F4303U, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com