

ES3DB R5G

est a Quote

ES3DB R5G Information

Heisener.com	Part Number	ES3DB R5G
	Manufacturer	TSC America Inc.
	Category	Discrete Semiconductor Products Diodes - Rectifiers - Single
	Description	DIODE, SUPER FAST, 3A, 200V, 35N
	Package	DO-214AA, SMB
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ES3DB R5G Specifications

Manufacturer Part NumberES3DB R5GManufacturerTSC America Inc.CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SingleDiodes - Rectifiers - SinglePackageDO-214AA, SMBSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ IfIV @ 3ASpeedFast Recovery < 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr10µA @ 200VCapacitance @ Vr, FSurface MountMounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA, SMBSupplier Device PackageSoc ~ 150°CCore of PackageSoc ~ 2150°C		
CategoryDiscrete Semiconductor ProductsDides - Rectifiers - SinglePackageDO-214AA, SMBSeries-Dide TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ IfIV @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr10µA @ 200VCurrent - Reverse Leakage @ Vr0px @ 200VCapacitance @ Vr, F46pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-55°C ~ 150°C	Manufacturer Part Number	ES3DB R5G
Noides - Rectifiers - SinglePackageDO-214AA, SMBSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ IfIV @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ VrI0µA @ 200VCapacitance @ Vr, FSurface MountMounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-55°C ~ 150°C	Manufacturer	TSC America Inc.
PackageDO-214AA, SMBSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Jo)3AVoltage - Forward (Vf) (Max) @ IfIV @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr10µA @ 200VCapacitance @ Vr, FSurface MountMounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-55°C ~ 150°C	Category	Discrete Semiconductor Products
Series-SeriesStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Jo)3AVoltage - Forward (Vf) (Max) @ IfIV @ 3ASpeedFast Recovery = < 500ns, > 200mA (Jo)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr10 μ A @ 200VCapacitance @ Vr, F46pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-55°C ~ 150°C		Diodes - Rectifiers - Single
Diode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ IfIV @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr10µA @ 200VCapacitance @ Vr, F46pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageJ00-214AA (SMB)Operating Temperature - Junction-55°C ~ 150°C	Package	DO-214AA, SMB
Voltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io) $3A$ Voltage - Forward (Vf) (Max) @ If $1V @ 3A$ SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr) $35ns$ Current - Reverse Leakage @ Vr $10\mu A @ 200V$ Capacitance @ Vr, F $46pF @ 4V, 1MHz$ Mounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction $-55^{\circ}C \sim 150^{\circ}C$	Series	-
Current - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ If1V @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr10μA @ 200VCapacitance @ Vr, F46pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-55°C ~ 150°C	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If $1V @ 3A$ SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr) $35ns$ Current - Reverse Leakage @ Vr $10\mu A @ 200V$ Capacitance @ Vr, F $46pF @ 4V, 1MHz$ Mounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction $-55^{\circ}C \sim 150^{\circ}C$	Voltage - DC Reverse (Vr) (Max)	200V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr10μA @ 200VCapacitance @ Vr, F46pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-55°C ~ 150°C	Current - Average Rectified (Io)	3A
Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr10μA @ 200VCapacitance @ Vr, F46pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-55°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	1V @ 3A
Current - Reverse Leakage @ Vr10μA @ 200VCapacitance @ Vr, F46pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-55°C ~ 150°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F46pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-55°C ~ 150°C	Reverse Recovery Time (trr)	35ns
Mounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-55°C ~ 150°C	Current - Reverse Leakage @ Vr	10µA @ 200V
Package / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-55°C ~ 150°C	Capacitance @ Vr, F	46pF @ 4V, 1MHz
Supplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-55°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction -55°C ~ 150°C	Package / Case	DO-214AA, SMB
	Supplier Device Package	DO-214AA (SMB)
Papert arrors ²	Operating Temperature - Junction	-55°C ~ 150°C
Report citors:		Report errors?

ES3DB R5G Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ES3DB R5G Payment Methods



ES3DB R5G Shipping Methods



If you have any question about ES3DB R5G, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com