



ESA30DTKH Information

Heisener.com

Part Number ESA30DTKH

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 60POS 0.125

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ESA30DTKH Specifications

Manufacturer Part Number ESA30DTKH Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 30 Number of Positions 60 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Loop Bellows Cotor Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	ESTISOD TIXII Specifications		
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 30 Number of Positions 60 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Loop Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Manufacturer Part Number	ESA30DTKH	
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 30 Number of Positions 60 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Loop Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Manufacturer	Sullins Connector Solutions	
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 30 Number of Positions 60 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Loop Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Category	Connectors, Interconnects	
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 30 Number of Positions 60 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Loop Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row30Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row30Number of Positions60Card Thickness $0.062"$ (1.57mm)Number of Rows2Pitch $0.125"$ (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $10\mu in (0.25\mu m)$ Contact TypeLoop BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, $0.125"$ (3.18mm) DiaOperating Temperature $-65°C \sim 125°C$	Series	-	
Number of Positions/Bay/Row30Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	30	
Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	60	
Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
Features Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Contact Finish Thickness 10μin (0.25μm) Contact Type Loop Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Number of Rows	2	
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness 10μ in $(0.25\mu$ m)Contact TypeLoop BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125 " $(3.18$ mm) DiaOperating Temperature -65 °C ~ 125 °C	Pitch	0.125" (3.18mm)	
Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Loop Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Features	-	
Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μ in $(0.25\mu$ m) Contact Type Loop Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125 " $(3.18$ mm) Dia Operating Temperature -65 °C ~ 125 °C	Mounting Type	Through Hole	
Contact Finish Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type $Loop Bellows$ Color $Blue$ Flange Feature $Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia$ Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Termination	Solder	
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Loop Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact Type Loop Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish	Gold	
Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature -65 °C ~ 125 °C	Contact Finish Thickness	10μin (0.25μm)	
Flange Feature Top Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature -65 °C ~ 125 °C	Contact Type	Loop Bellows	
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Blue	
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	-65°C ~ 125°C	
			Report errors?

ESA30DTKH Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ESA30DTKH Payment Methods



















ESA30DTKH Shipping Methods













If you have any question about ESA30DTKH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com