

ESC08DRTH-S13

est a Quote

ESC08DRTH-S13 Information

Heisener.com	Part Number	ESC08DRTH-S13
	Manufacturer	Sullins Connector Solutions
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors
	Description	CONN EDGE DUAL FMALE 16POS 0.100
	Package	-
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESC08DRTH-S13 Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, Edgeboard ConnectorsPackage-Package-Series-Card TypeMon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions/Bay/Row16Card Tytek0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)FeaturesGoald Edge, Straddle MountMounting TypeSolderContact ThinknessSolderContact Finish ThicknessGoldContact Finish ThicknessIupin (0.52µm)Contact TypeFealuesContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderFange FeatureSolon Contact, SolderFange FeatureSolon Contact, SolderColorBueColorSolon Contact, SolderColorSolon Contact, SolderColorSolo			
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions/Bay/Row16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesGoald Edge, Straddle MountFeaturesSolderContact MaterialSolderContact Finish Thickness10µin (0.25µm)Contact TypeGoldContact TypeFull BellowsContact TypeSuleContact TypeSuleContact TypeFull BellowsContact TypeSuleColorBueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-5°C ~ 125°C	Manufacturer Part Number	ESC08DRTH-S13	
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialPhosphor BronzeContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Kounting TypeBoard Edge, Straddle MountContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeFull BellowsColorBueFinage FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions/Bay/Row16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialSolderContact Finish ThicknessGoldContact TypeFull BellowsContact TypeFull BellowsColorBueColorGoldout Copening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-	
Number of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions 16 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Type Full Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	8	
Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	16	
Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeBuleColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2	
Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)	
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	Card Extender	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Board Edge, Straddle Mount	
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder	
Contact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold	
Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10µin (0.25µm)	
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Full Bellows	
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Blue	
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	-65°C ~ 125°C	
		Report errors	

ESC08DRTH-S13 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ESC08DRTH-S13 Payment Methods





If you have any question about ESC08DRTH-S13, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com