

ESC49DRTN

ESC49DRTN Information

Heisener.com	Part Number Manufacturer Category Description Package	ESC49DRTN Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 98POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESC49DRTN Specifications

Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row49Number of Positions98Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness10µin (0.25µm)Contact Finish ThicknessFull BellowsContact TypeHoleContact Finish Thickness10µin (0.25µm)Contact TypeSulderContact TypeSolderContact TypeSulderContact TypeGoldContact TypeSulderColorBlueFange Feature-Operating Temperature-65°C ~ 125°C	-	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row49Number of Positions0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.5µm)Contact TypeFull BellowsContact TypeSull Sci	Manufacturer Part Number	ESC49DRTN
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row49Number of Positions0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness10/ui (0.25µm)Contact Finish Thickness10/uin (0.25µm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-5°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row49Number of Positions98Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness10/uin (0.25µm)Contact TypeFull BellowsContact Type50ldeContact Type50ldeContact Type50ldeContact Type50ldeContact Type60dContact Type50ldeContact Type50ldeContact Type60dContact Type50ldeContact Type50lde <t< td=""><td>Category</td><td>Connectors, Interconnects</td></t<>	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row49Number of Positions98Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness10µin (0.25µm)Contact Finish ThicknessFull BellowsContact TypeHoleContact Finish Thickness10µin (0.25µm)Contact TypeSulderContact TypeSolderContact TypeSulderContact TypeGoldContact TypeSulderColorBlueFange Feature-Operating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row49Number of Positions98Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBueFage Feature-Operating Temperature65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row49Number of Positions98Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Features-Mounting Type0.100° (2.54mm)Contact FinishSolderContact FinishGoldContact Finish ThicknessGoldContact TypeHulle JosepColorBile JosepFange Feature-Pogenting Themperature6°C ~ 125°C	Series	-
Number of Positions/Bay/Row49Number of Positions98Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type1/100 HoleTerminationSolderContact MaterialGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBueFlange Feature-ColorSiderFlange Feature-Cortact SpectrumSiderContact Spectrum-ColorSiderColorSiderColorSiderColorSiderColorSiderColorSiderColorSiderStater-ColorSiderColorSiderSiderSiderStater-ColorSiderSiderSiderSiderSiderSiderSiderColorSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSiderSider<	Card Type	Non Specified - Dual Edge
Number of Positions 98 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type - Mounting Type Through Hole Contact Material Solder Contact Finish Gold Contact Finish Thickness I/lupin (0.25µm) Color Full Bellows Color Blue Flange Feature - Operating Temperature -	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeFull BellowsColorBueFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	49
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessJujin (0.25µm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions	98
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlueFlange Feature-Operating Temperature65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessI/µin (0.25µm)Contact TypeBlueColorBlueFlange Feature-Operating Temperatures65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-5°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFul BellowsColorBlueFlange Feature-Operating Temperature65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature65°C ~ 125°C	Termination	Solder
Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Contact Finish	Gold
ColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Contact Finish Thickness	10µin (0.25µm)
Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Blue
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

ESC49DRTN Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ESC49DRTN Payment Methods



ESC49DRTN Shipping Methods



If you have any question about ESC49DRTN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com