

ESC50DRYI-S13

uest a Quote

ESC50DRYI-S13 Information

| Heisener.com | Part Number | ESC50DRYI-S13 |
|--------------------|--------------|---|
| | Manufacturer | Sullins Connector Solutions |
| | Category | Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors |
| | Description | CONN EDGE DUAL FMALE 100POS .100 |
| | Package | - |
| | | For the pricing/inventory/lead time, please contact |
| For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESC50DRYI-S13 Specifications

| ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions0.062" (1.57mm)Number of Rows2PitchO.100" (2.54mm)FeaturesGoldeMounting TypeBoard Edge, Straddle MountTerminationSolderContact Finish ThicknessJujin (0.25µm)Contact Finish ThicknessIujin (0.25µm)Contact TypeFell BellowsContact TypeSolderContact Finish ThicknessJujin (0.25µm)Contact Finish ThicknessJujin (0.25µm)Contact TypeSolderContact Finish ThicknessJujin (0.25µm)Contact Finish ThicknessJujin (0.25µm)Contact TypeFull BellowsContact TypeFull BellowsContact TypeSolderContact TypeFull BellowsContact TypeSolwContact Type< | _ | |
|---|-----------------------------|---|
| CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesGoald Edge, Straddle MountMounting TypeBoard Edge, Straddle MountContact MaterialSolderContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeSolderContact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature65°C ~ 125°C | Manufacturer Part Number | ESC50DRYI-S13 |
| Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialPhosphor BronzeContact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeFull BellowsContact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Manufacturer | Sullins Connector Solutions |
| Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialGoldContact Finish Thickness10µin (0.25µm)Contact Finish ThicknessGoldContact TypeHug BellowsColorBueFlage FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Category | Connectors, Interconnects |
| Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions/Bay/Row100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact FinishSolderContact Finish Thickness10µin (0.25µm)Contact Finish ThicknessFeal BealContact TypeSolderContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-50°C ~ 125°C | | Card Edge Connectors - Edgeboard Connectors |
| Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact Finish ThicknessGoldContact Finish ThicknessI0µin (0.25µm)Contact TypeFull BellowsColorBueFalage FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Package | - |
| GenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact FinishGoldContact Finish ThicknessIoµin (0.25µm)Contact TypeFull BellowsColorBueFage FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Series | - |
| Number of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialGoldContact Finish Thickness10µin (0.25µm)Contact Finish ThicknessBuleColorBuleFaluge FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Card Type | Non Specified - Dual Edge |
| Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Gold Contact Finish Thickness I0µin (0.25µm) Contact Type Full Bellows Color Blue Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C | Gender | Female |
| Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Number of Positions/Bay/Row | 50 |
| Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Number of Positions | 100 |
| Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)ColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Card Thickness | 0.062" (1.57mm) |
| FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessIoµin (0.25µm)Contact TypeBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Number of Rows | 2 |
| Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Pitch | 0.100" (2.54mm) |
| TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Features | Card Extender |
| Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Mounting Type | Board Edge, Straddle Mount |
| Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Termination | Solder |
| Contact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Contact Material | Phosphor Bronze |
| Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Contact Finish | Gold |
| ColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Contact Finish Thickness | 10μin (0.25μm) |
| Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Contact Type | Full Bellows |
| Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$ | Color | Blue |
| | Flange Feature | Top Mount Opening, Threaded Insert, 4-40 |
| Report errors? | Operating Temperature | $-65^{\circ}C \sim 125^{\circ}C$ |
| | | Report errors? |

ESC50DRYI-S13 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ESC50DRYI-S13 Payment Methods



ESC50DRYI-S13 Shipping Methods



If you have any question about ESC50DRYI-S13, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com